



Der Vertrieb der PanAcoustics Produkte erfolgt durch den autorisierten Fachhandel. Fragen Sie uns an, wir helfen Ihnen sehr gerne weiter.

Standard colours: RAL 9006 (aluminium) or RAL-9010 (white) or RAL-9005 (black)


Pan Beam – PB 04 MKII Series

	PB 04 MKII	Standard version: Compact active digitally controllable column speaker with Beam Steering Technology, Drivers: 4 x 3.5 "wide band chassis, amplifier output power: 4 x up to 100 watt, Pan Beam network I/O: EtherCon RJ 45 for 2x analog line input, controll data and error detection, PSU: 110V / 230V with IEC 60320-1 C13 connector	<u>C3</u>	
	PB 04-AES/EBU MKII	As PB 04 but with EtherCon RJ 45 for 2x AES/EBU mono input	<u>C3</u>	
	PB 04-D MKII	As PB 04 but with DANTE module, DANTE Primary and Secondary Port: 2x EtherCon RJ 45 (2 x audio streams, controll data), Pan Beam Net Link Port	<u>C3</u>	
	PB 04-D PoE MKII	As PB 04-D but with Power via PoE (60W max.)	<u>C3</u>	
	PB 04-100V MKII	As PB 04 but with 2 x 100V Input (terminal loudspeaker clamp)	<u>C3</u>	
	PB 04-100V-DC input MKII	As PB 04 but with 2 x 100V Input (terminal clamp), additional 24V DC input	<u>C3</u>	

Pan Beam – PB 08 MKII Series

	PB 08 MKII Standard Version: Compact active digitally controllable column speaker with Beam Steering Technology, Drivers: 8 x 3.5 "wide band chassis, amplifier output power: 8 x up to 100 watt, Pan Beam network I/O: EtherCon RJ 45 for 2x analog line input, controll data and error detection, PSU: 110V / 230V with IEC 60320-1 C13 connector	<u>C3</u>	
	PB 08-R MKII As PB 08 but as rental version with PSU: 110V / 230V with TrueCon connector. Standard colour: RAL 9005 black	<u>C3</u>	
	PB 08-AES/EBU MKII As PB 08 but with EtherCon RJ 45 for 2x AES/EBU mono input	<u>C3</u>	
	PB 08-D MKII As PB 08 but with DANTE module, DANTE Primary and Secondary Port: 2x EtherCon RJ 45 (2 x audio streams, controll data), Pan Beam Net Link Port	<u>C3</u>	
	PB 08-D PoE MKII As PB 08-D MKII but with Power via PoE (100W max.)	<u>C3</u>	
	PB 08-100V MKII As PB 08 but with 2 x 100V Input (terminal loudspeaker clamp)	<u>C3</u>	
	PB 08-100V-DC input MKII As PB 08 but with 2 x 100V Input (terminal loudspeaker clamp), additional 24/48V DC input (cable gland)	<u>C3</u>	

Pan Beam – PB 16 MKII Series

	PB 16 MKII	Standard version: Compact active digitally controllable column speaker with Beam Steering Technology, Drivers: 16 x 3.5 "wide band chassis, amplifier output power: 16 x up to 100 watt, Pan Beam network I/O: EtherCon RJ 45 for 2x analog line input, controll data and error detection, PSU: 110V / 230V with IEC 60320-1 C13 connector, PB 16 consists of two modules with internal link	<u>C3</u>	
	PB 16-AES/EBU MKII	As PB 16 MKII but with EtherCon RJ 45 for 2x AES/EBU mono input	<u>C3</u>	
	PB 16-D MKII	As PB 16 MKII but with DANTE module, DANTE Primary and Secondary Port: 2x EtherCon RJ 45 (2 x audio streams, controll data), Pan Beam Net Link Port	<u>C3</u>	
	PB 16-100V MKII	As PB 16 MKII but with 2 x 100V Input (terminal loudspeaker clamp)	<u>C3</u>	
	PB 16-100V-DC input MKII	As PB 16 MKII but with 2 x 100V Input (terminal loudspeaker clamp), additional 24/48V DC input (cable gland)	<u>C3</u>	

Pan Beam – PB 16 MKII (ohne housing)

PB 16 MKII (one housing)	(one housing) Standard Version: As PB 16 MKII in one housing with 2 seperated grills	<u>C3</u>	
PB 16-AES/EBU MKII (one housing)	As PB 16 MKII (one housing), EtherCon RJ 45 for 2x AES/EBU mono input	<u>C3</u>	
PB 16-D MKII (one housing)	As PB 16 MKII (one housing) with DANTE module, DANTE Primary and Secondary Port: 2x EtherCon RJ 45 (2 x audio streams, controll data), Pan Beam Net Link Port	<u>C3</u>	
PB 16-100V MKII (one housing)	As PB 16 MKII (one housing) with 2 x 100V Input (terminal loudspeaker clamp)	<u>C3</u>	
P 16-100V-DC input MKII (one housing)	As PB 16 MIKK (one housing) with 2 x 100V Input (terminal loudspeaker clamp), additional 24/48V DC input	<u>C3</u>	


Pan Beam – PB 16-C MKII Series

	PB 16-C MKII Standard Version: Compact active digitally controllable column speaker with Beam Steering Technology, Drivers: 16 x 3.5 "wide band chassis, amplifier output power: 16 x up to 40 watt, Pan Beam network I/O: EtherCon RJ 45 for 2x analog line input, controll data and error detection, PSU: 110V / 230V with IEC 60320-1 C13 connector, PB 16-C consists of two modules with internal link	C3	
	PB 16-C-AES/EBU MKII As PB 16-C MKII, EtherCon RJ 45 for 2x AES/EBU mono input	C3	

Pan Beam – PB 16-C (one housing) MKII Series

	PB 16-C MKII (one housing) Standard Version: As PB 16-C MKII in one housing with 2 seperated grills	C3	
	PB 16-C-AES/EBU MKII (one housing) As PB 16-C MKII (one housing), EtherCon RJ 45 for 2x AES/EBU mono input	C3	


Pan Beam – PB 24 MKII Series

	PB 24 MKII	Standard version: Compact active digitally controllable column speaker with Beam Steering Technology, Drivers: 24 x 3.5 "wide band chassis, amplifier output power: 24 x up to 100 watt, Pan Beam network I/O: EtherCon RJ 45 for 2x analog line input, controll data and error detection, PSU: 110V / 230V with IEC 60320-1 C13 connector, PB 24 consists of three modules with internal link	<u>C3</u>
	PB 24-AES-EBU MKII	As PB 24 MKII but with EtherCon RJ 45 for 2x AES/EBU mono input	<u>C3</u>
	PB 24-D MKII	As PB 24 MKII but with DANTE module, DANTE Primary and Secondary Port: 2x EtherCon RJ 45 (2 x audio streams, controll data), Pan Beam Net Link Port	<u>C3</u>
	PB 24-100V MKII	As PB 24 MKII but with 2 x 100V Input (terminal loudspeaker clamp)	<u>C3</u>
	PB 24-100V-DC input MKII	As PB 24 MKII but with 2 x 100V Input (terminal loudspeaker clamp), additional 24/48V DC input (cable gland)	<u>C3</u>

Pan Beam – PB 24 MKII (one housing) Series

PB 24 MKII (one housing)	Standard version: As PB 24 MKII in one housing with 3 seperated grills	<u>C3</u>
PB 24-AES/EBU MKII (one housing)	As PB 24 MKII (one housing) but with EtherCon RJ 45 for 2x AES/EBU mono input	<u>C3</u>
PB 24-D MKII (one housing)	As PB 24 MKII (one housing) but with DANTE module, DANTE Primary and Secondary Port: 2x EtherCon RJ 45 (2 x audio streams, controll data), Pan Beam Net Link Port	<u>C3</u>


Pan Beam – PB 32 MKII Series

	PB 32 MKII	Standard version: Compact active digitally controllable column speaker with Beam Steering Technology, Drivers: 32 x 3.5 "wide band chassis, amplifier output power: 32 x up to 100 watt, Pan Beam network I/O: EtherCon RJ 45 for 2x analog line input, controll data and error detection, PSU: 110V / 230V with IEC 60320-1 C13 connector, PB 32 consists of three modules with internal link	<u>C3</u>	
	PB 32-AES/EBU MKII	As PB 32 MKII but with EtherCon RJ 45 for 2x AES/EBU mono input	<u>C3</u>	
	PB 32-D MKII	As PB 32 MKII but with DANTE module, DANTE Primary and Secondary Port: 2x EtherCon RJ 45 (2 x audio streams, controll data), Pan Beam Net Link Port	<u>C3</u>	
	PB 32-100V MKII	As PB 32 MKII but with 2 x 100V Input (terminal loudspeaker clamp)	<u>C3</u>	
	PB 32-100V-DC input MKII	As PB 32 MKII with 2 x 100V Input (terminal clamp), additional 24/48V DC input	<u>C3</u>	


Pan Beam – PB 40 MKII Series

	PB 40 MKII	Standard version: Compact active digitally controllable column speaker with Beam Steering Technology, Drivers: 40 x 3.5 "wide band chassis, amplifier output power: 40 x up to 100 watt, Pan Beam network I/O: EtherCon RJ 45 for 2x analog line input, controll data and error detection, PSU: 110V / 230V with IEC 60320-1 C13 connector, PB 40 consists of three modules with internal link	<u>C3</u>	
	PB 40-AES/EBU MKII	As PB 40 MKII but with EtherCon RJ 45 for 2x AES/EBU mono input	<u>C3</u>	
	PB 40-D MKII	As PB 40 MKII but with DANTE module, DANTE Primary and Secondary Port: 2x EtherCon RJ 45 (2 x audio streams, controll data), Pan Beam Net Link Port	<u>C3</u>	
	PB 40-100V MKII	As PB 40 MKII but with 2 x 100V Input (terminal loudspeaker clamp)	<u>C3</u>	
	PB 40-100V-DC input MKII	As PB 40 MKII with 2 x 100V Input (terminal clamp), additional 24/48V DC input	<u>C3</u>	



Pan Beam – PB 224 Series

	PB 224	Standard version: Compact active digitally controllable 2-way line speaker system, Drivers: 6 x 6.5" HiQ cone, 18 x 1" HiQ RF neodymium drivers, amplifier output power: 12 x up to 100 Watt, Pan Pan Beam network I/O: 2 x EtherCon RJ 45 for 2x analog line input, controll data and error detection, PSU: 110V / 230V, Connectors: PowerCon true 1 (input + link out)	<u>C3</u>	
	PB 224-AES/EBU	As PB 224 with EtherCon RJ 45 for 2x AES/EBU mono input	<u>C3</u>	
	PB 224-D	As PB 224 with DANTE module, DANTE Primary and Secondary Port: 2x EtherCon RJ 45 (2 x audio streams, controll data), Pan Beam Net Link Port	<u>C3</u>	
	PB 224-100V	As PB 224 with 2 x 100V Input (terminal loudspeaker clamp)	<u>C3</u>	
	PB 224-100V-DC input	As PB 224 with 2 x 100V Input (terminal clamp), additional 24/48V DC input	<u>C3</u>	



Pan Beam – PB 248 Series

	PB 248 Standard version: Consists of two PB 224 modules and link kit	<u>C3</u>
	PB 248-AES/EBU Consists of two PB 224 - AES/EBU modules and link kit	<u>C3</u>
	PB 248-D Consist of PB 224-D Module + Slave Module and link kit	<u>C3</u>
	PB 248-100V Consist of two PB 224 - 100 V modules and link kit	<u>C3</u>
	PB 248-100V-DC input Consists of two PB 224 - 100 V / DC	<u>C3</u>





Pan Beam – PB S-xxx Subwoofer Series

	PB S-208 MKII	Standard version: Double 8" band-pass subwoofer, including DSP and amp, frequency range: 42 Hz to 120 Hz, 600 Watt (program), 800 Watt (peak), Pan Pan Beam network I/O: 2 x EtherCon RJ 45 for 2x analog line input, control data and error detection, PSU: 110V / 230V, connection type: 1 x PowerCon True 1, Birch plywood enclosure, standard colour: RAL 9005 black / textured finish	<u>C3</u>	
	PB S-208-AES-EBU MKII	As PB S-208 with EtherCon RJ 45 for 2x AES/EBU mono input	<u>C3</u>	
	PB S-208-D MKII	As PB S-208 with DANTE module, DANTE Primary and Secondary Port: 2x EtherCon RJ 45 (2 x audio streams, control data), Pan Beam Net Link Port	<u>C3</u>	
	PB S-118	Standard version: Single 18" subwoofer including DSP and amp, frequency range: 35 Hz to 130 Hz, 1000 watt (programm), 2000 watt (peak), Pan Pan Beam network I/O: 2 x EtherCon RJ 45 for 2x analog line input, control data and error detection, PSU: 110V / 230V, connection type: 1 x PowerCon True 1, Birch plywood enclosure, standard colour: RAL 9005 black / textured finish	<u>C3</u>	
	PB S-118-AES-EBU	As PB S-118 with EtherCon RJ 45 for 2x AES/EBU mono input	<u>C3</u>	
	PB S-118-D	As PB S-118 with DANTE module, DANTE Primary and Secondary Port: 2x EtherCon RJ 45 (2 x audio streams, control data), Pan Beam Net Link Port	<u>C3</u>	


Colour option (RAL-XXXX, powder coated, three gloss levels)

 	The painting refers to housing and grids in the same colour, different colours (housing, grid) are available on request.		
	CO 04	Colour option RAL-xxxx for Px 04-x	<u>C3</u>
	CO 08	Colour option RAL-xxxx for Px 08-x	<u>C3</u>
	CO 16	Colour option RAL-xxxx for Px 16-x	<u>C3</u>
	CO 24	Colour option RAL-xxxx for Px 24-x	<u>C3</u>
	CO 32	Colour option RAL-xxxx for Px 32-x	<u>C3</u>
	CO 40	Colour option RAL-xxxx for Px 40-x	<u>C3</u>
	CO 224	Colour option RAL-xxxx for Px 224	<u>C3</u>
	CO 248	Colour option RAL-xxxx for Px 248	<u>C3</u>
	CO wall mount	Colour option RAL-xxxx for wall mount or slider sets	<u>C3</u>
	CO subwoofer	Colour option RAL-xxxx for subwoofer	<u>C3</u>
	CO screws	Colour option RAL-xxxx for screws from slider, wall mount, etc.	<u>C3</u>
	Default colour for all Pan Beam products is aluminium RAL 9006, or RAL-9010 (white) or RAL-9005 (black), unless an other colour information is specified for a product. Usually all products are powdered. colour have to choose by order, with RAL xxxx (4-bit code) and gloss level. Other colour systems are possible, like RAL (3-bit code), NCS, Pantone, DB etc, on request.		














Pan Beam Net - Interfaces






	PanCon Blue	Converter USB to PanBeamNet for setup and audio connection. Audioinput 2x XLR 3-Pin female connector for analog and digital audiosignals (symmetric). Pan Beam Net connection (RJ 45)	<u>C3</u>
	PanSplitter 2/6	Pan Beam 19" rack mount network switch, Connections: 2 x XLR female, USB (B), RS 485 (Phoenix), Outputs: 6 x EtherCon (Pan Beam network, incl. both Audiofeeds A and B), 1 x alarm contact, RS 485 input for media control, incl. Rack Mount	<u>C3</u>
	PanSplitter 4/4	Pan Beam 19" rack mount network switch, Connections: 4 x XLR female, USB (B), RS 485 (Phoenix), Outputs: 4 x EtherCon (Pan Beam network, only one Audiofeed (A)), AES/EBU ready, 1 x alarm contact, RS 485 input for media control, incl. Rack Ears	<u>C3</u>
	Pan Beam Net Preset Selector	19" rack mount preset activation unit. Direct selection of 5 stored presets + mute in the Pan Beam devices.	<u>C3</u>







Pan Beam Options

	Pilotone evaluation	22kHz Pilot-tone and fault signal contact, available for all Pan Beam units	<u>C3</u>
---	----------------------------	---	-----------

Accessories

	wall mount, fix, PB xx MKII	Wall-mount kit for mounting Pan Column-Speaker on wall, PB 04, PB 08, P 04-Pi, P 08-Pi, P 8-15-Pi. (Art. 801839)	<u>C3</u>
	wall mount, turnable, PB xx, MKII	Swivel wall-mount kit for mounting Pan Column-Speaker on Wall (bottom and top) P 04-Pi, P 08-Pi, P 8-15-Pi, PB 04, PB 08 in stainless Steel. (Art. 801840)	<u>C3</u>
	wall mount, horizontal turnable, PB xx (TWM III)	Wall-mount horizontal turnable kit for mounting Pan Column-Speaker on wall, PB 04, PB 08, P 04-Pi, P 08-Pi, P 8-15-Pi. 2 pcs for: PB 16, PB 24. (Art. 801841)	<u>C3</u>
	stand holder MKII, PB xx	Stand mount (35mm), stainless steel for: P 01-Pi, P 02-Pi, P 04-Pi, P 08-Pi, P 8-15-Pi, PB 04, PB 08, PB 16. (Art. 801843)	<u>C3</u>
	slider set, PB xx MKII	Slider set, consist of 2 x PB xx slider, to connect two PB xx together (Art. 801924)	<u>C3</u>
	Adaptor cover mounting PB xx	For floor or ceiling mount (Art. 802459)	<u>C3</u>
	Spacer 50mm	For wall mount, when using Buccaneer connections (IP65 and 100V Versions) in combination with wall mount 801839 or 801841, stainless steel (Art. 802822)	<u>C3</u>
	wall mount, turnable PB 224, black	Turnable Wall Mount for PB 224 incl. mounting kit. The wall mount enables horizontal orientation included, standard colour: black (Art. 801314)	<u>C3</u>
	wall mount, turnable PB 224, white	Turnable Wall Mount for PB 224 incl. mounting kit. The wall mount enables horizontal orientation included, standard colour: white (Art. 802833)	<u>C3</u>
	mounting plate, PB 2xx WMP	PB 223, wall mount kit, consist of adapter plate and 2 x PB 224 slider (Art. 800388)	<u>C3</u>
	stand holder, PB 224	Stand mount (35mm) for PB 224 (Art. 800392)	<u>C3</u>
	Adaptor cover mounting PB 224	For floor or ceiling mount (Art. 802858)	<u>C3</u>
	slider set, PB 2xx	Connection kit, consist of 4 x PB 224 slider, to connect two PB 224 together (Art. 800393)	<u>C3</u>

	PB 2xx grid	Grid to fly up to 5 PB 224 modules	<u>C3</u>	
	PB 2xx flyware	Flyware für PB 224	<u>C3</u>	
	wall mount, tiltable, turnable (black)	Universal wall mount (horizontal 180° and vertical 0-15° adjustment), up to 10 kg load, incl. Sliding block, colour: RAL 9005 black (Art. 801449)	<u>C3</u>	
	wall mount, tiltable, turnable (white)	Universal wall mount (horizontal 180° and vertical 0-15° adjustment), up to 10 kg load, incl. Sliding block, standard colour: white (art. 801450)	<u>C3</u>	
	Rain Hood Px 208	Weather protection fabric for outdoor use. Suitable for bass speakers: PB S-208 and P S-208	<u>C3</u>	
	Rain Hood Px 118	Weather protection fabric for outdoor use. Suitable for bass speakers: PB S-118 and P S-118	<u>C3</u>	
	pole mount PBxx	Mounting bracket for P/PB 08, PB 16, on poles (art. 802370), stainless steel. Note: Tension straps for attaching to the mast are not included in the bracket.	<u>C3</u>	
	Speaker tilt connector „RingLock“	For speaker stands with tube diameter of 35 mm. A unique patented expanding mandrel system provides a tight and firm fit for the speaker. The moveable plastic splints separate the speaker from the stand creating a vibration-free connection. Easy to use ring lock. Colour black (art. 802349).	<u>C3</u>	
	speaker stand with plate RingLock (black)	speaker stand with patented expanding mandrel system that provides a stable, tight and firm fit for speakers. Connecting the speaker is easy and is done using the handy ring lock - which is simply placed in position and screwed on. Heavy cast iron plate with a relatively small diameter. The tried-and-tested spring-loaded bolt with locking screw makes height adjustment easy and safe. Max. height 1.800 mm, suitable for speakers with max. 20 kg. standard colour: black (art. 801488)	<u>C3</u>	

	speaker stand with plate (white)	A decorative space saving speaker stand. The heavy cast iron plate with a relatively small diameter requires little space. The tried-and-tested spring-loaded bolt with locking screw makes height adjustment easy and safe. The stand has a maximum pull-out height of 1800 mm and is suitable for speakers with a maximum weight of 20 kg. The integrated mounting aid simplifies mounting the loud speaker cabinets. standard colour: white (art. 801580)	<u>C3</u>	
	speaker stand with plate (black)	A decorative space saving speaker stand. The heavy cast iron plate with a relatively small diameter requires little space. The tried-and-tested spring-loaded bolt with locking screw makes height adjustment easy and safe. The stand has a maximum pull-out height of 1800 mm and is suitable for speakers with a maximum weight of 20 kg. The integrated mounting aid simplifies mounting the loud speaker cabinets. standard colour: black (art. 801581)	<u>C3</u>	
	ceiling mount, fix, (white) PB xx	Robust and useful loudspeaker ceiling mount with 250 mm distance and internal cable management. The swivel area is +/- 45°. Within the parameters - the settings range from 0 to 45°. The clamping bracket is for loudspeakers with a vertical mounting template from 70 to 76.2 mm. For other attachment possibilities additional adapter brackets are available. A mounting bracket with side and central cable management makes mounting to the ceiling easier. incl. slider block, colour: standard colour: white (art. 801452)	<u>C3</u>	
	ceiling mount, fix, (black) PB xx	Robust and useful loudspeaker ceiling mount with 250 mm distance and internal cable management. The swivel area is +/- 45°. Within the parameters - the settings range from 0 to 45°. Max. load is 25kg. The clamping bracket is for loudspeakers with a vertical mounting template from 70 to 76.2 mm. For other attachment possibilities additional adapter brackets are available. A mounting bracket with side and central cable management makes mounting to the ceiling easier. incl. slider block, standard colour: black (art. 801451)	<u>C3</u>	
	ceiling mount, flex, (black) PB xx	Flexible ceiling mount with variable length 700-1200mm incl. slider block, standard colour: black (art. 802406)	<u>C3</u>	
	ceiling mount, flex, (white) PB xx	Flexible ceiling mount with variable length 700-1200mm incl. slider block, standard colour: white (art. 801285)	<u>C3</u>	

**Ersetzt alle bisherigen Preislisten.
Remplace tous les listes de prix anciennes.**

**Artikel mit grau unterlegtem Händlercode sind Neuheiten oder haben eine Preisänderung erfahren.
Articles avec code client gris sont des nouveautés ou ont changé de prix.**

**Bei Artikeln mit unterstrichenem Händlercode bitte Verfügbarkeit anfragen!
Articles avec code client souligné demandez leur disponibilité!**