



Der Vertrieb der PanAcoustics Produkte erfolgt durch den autorisierten Fachhandel. Fragen Sie uns an, wir helfen Ihnen sehr gerne weiter.

Standard colours: RAL 9006 (aluminium) or RAL-9010 (white) or RAL-9005 (black)


Pan Powerline - MKII Series

	PB 04-PPL MKII	Compact active digitally controllable column speaker with Beam Steering Technology, Drivers: 4 x 3.5 "wide band chassis, amplifier output power: 4 x up to 40 watt, Pan Powerline I/O: 2 x Two-wire connector (audio, controll data and power)	<u>C3</u>	
	PB 08-PPL MKII	Compact active digitally controllable column speaker with Beam Steering Technology, Drivers: 8 x 3.5" wide band chassis, amplifier output power: 8 x up to 40 watt, Pan Powerline I/O: 2 x Two-wire connector (audio, controll data and power)	<u>C3</u>	
	PB 16-C-PPL MKII	Compact active digitally controllable column speaker with Beam Steering Technology, Drivers: 16 x 3.5 "wide band chassis, amplifier output power: 16 x up to 20 watt, Pan Powerline I/O: 2 x Two-wire connector (audio, controll data and power), PB 16-C-PPL consist fo tow modules with internal link	<u>C3</u>	
	PB 16-C-PPL MKII (one housing)	Compact active digitally controllable column speaker with Beam Steering Technology, Drivers: 16 x 3.5 "wide band chassis, amplifier output power: 16 x up to 20 watt, Pan Powerline I/O: 2 x Two-wire connector (audio, controll data and power)	<u>C3</u>	







Pan Powerline – Control Unit Series



	CCU 2/2-PPL	Central control unit for Pan Powerline system, with two Powerline outputs (each 200 Watt), each Output has a separate audio input (XLR), preset selector for switching stored presets at connected devices, interface for external media control	<u>C3</u>	
	CCU 4/4 PPL	Central control unit for Pan Powerline system, with four Powerline outputs (each 200 Watt), each Output has a separate audio input (XLR), preset selector for switching stored presets at connected devices, interface for external media control	<u>C3</u>	

Colour option (RAL-XXXX, powder coated, three gloss levels)

	The painting refers to housing and grids in the same colour, different colours (housing, grid) are available on request.		
	CO 04	Colour option RAL-xxxx for Px 04-x	<u>C3</u>
	CO 08	Colour option RAL-xxxx for Px 08-x	<u>C3</u>
	CO 16	Colour option RAL-xxxx for Px 16-x	<u>C3</u>
	CO wall mount	Colour option RAL-xxxx for wall mount (without screws)	<u>C3</u>
Default colour for all Pan Beam products is aluminium RAL 9006, or RAL-9010 (white) or RAL-9005 (black), unless an other colour information is specified for a product. Usually all products are powdered. colour have to choose by order, with RAL xxxx (4-bit code) and gloss level. Other colour systems are possible, like RAL (3-bit code), NCS, Pantone, DB etc, on request.			

Mounting accessories

	wall mount, fix, PB xx MKII	Wall-mount kit for mounting Pan Column-Speaker on wall, PB 04, PB 08, P 04-Pi, P 08-Pi, P 8-15-Pi. (Art. 801839)	<u>C3</u>
	wall mount, turnable, PB xx, MKII	Swivel wall-mount kit for mounting Pan Column-Speaker on Wall (bottom and top) P 04-Pi, P 08-Pi, P 8-15-Pi, PB 04, PB 08 in stainless Steel. (Art. 801840)	<u>C3</u>
	wall mount, horizontal turnable, PB xx (TWM III)	Wall-mount horizontal turnable kit for mounting Pan Column-Speaker on wall, PB 04, PB 08, P 04-Pi, P 08-Pi, P 8-15-Pi. 2 pcs for: PB 16, PB 24. (Art. 801841)	<u>C3</u>
	stand holder MKII, PB xx	Stand mount (35mm), stainless steel for: P 01-Pi, P 02-Pi, P 04-Pi, P 08-Pi, P 8-15-Pi, PB 04, PB 08, PB 16. (Art. 801843)	<u>C3</u>
	wall mount, tiltable, turnable (black)	Universal wall mount (horizontal 180° and vertical 0-15° adjustment), up to 10 kg load, incl. Sliding block, standard colour: black (Art. 801449)	<u>C3</u>
	wall mount, tiltable, turnable (white)	Universal wall mount (horizontal 180° and vertical 0-15° adjustment), up to 10 kg load, incl. Sliding block, standard colour: white (art. 801450)	<u>C3</u>
	ceiling mount, fix, (black) PB xx	Robust and useful loudspeaker ceiling mount with 250 mm distance and internal cable management. The swivel area is +/- 45°. Within the parameters - the settings range from 0 to 45°. Max. load is 25kg. The clamping bracket is for loudspeakers with a vertical mounting template from 70 to 76.2 mm. For other attachment possibilities additional adapter brackets are available. A mounting bracket with side and central cable management makes mounting to the ceiling easier. incl. slider block, standard colour: black (art. 801451)	<u>C3</u>
	Ceiling mount, fix, (white) PB xx	Dito ceiling mount, fix, (black) PB xx but white (art. 801452)	<u>C3</u>

	<p>Telescop ceiling mount, flex, (black) PB xx</p> <p>Flexible ceiling mount with variable length 700-1200mm incl. slider block, standard colour: black (art. 802406)</p>	<p><u>C3</u></p>	
	<p>Telescop ceiling mount, flex, (white) PB xx</p> <p>Flexible ceiling mount with variable length 700-1200mm incl. slider block, standard colour: white (art. 801285)</p>	<p><u>C3</u></p>	

**Ersetzt alle bisherigen Preislisten.
Remplace tous les listes de prix anciennes.**

**Artikel mit grau unterlegtem Händlercode sind Neuheiten oder haben eine Preisänderung erfahren.
Articles avec code client gris sont des nouveautés ou ont changé de prix.**

**Bei Artikeln mit unterstrichenem Händlercode bitte Verfügbarkeit anfragen!
Articles avec code client souligné demandez leur disponibilité!**