



**Der Vertrieb der PanAcoustics Produkte erfolgt durch den autorisierten Fachhandel. Fragen Sie uns an, wir helfen Ihnen sehr gerne weiter.**

**Standard colours: RAL 9006 (aluminium) or RAL-9010 (white) or RAL-9005 (black)**



### Pan Speaker – P 01-Pi MKII Series

	<b>P 01-Pi MKII</b>	2-way passive compact loudspeaker with design aluminium housing, Drivers: 1 x high power LF 3.5" and RF of 0.5" coax, Power handling: 50 watt (program), 80 watt (peak) 4 ohm. Connections: 1 x two wire connector, delivery incl. U-bracket	<u>C3</u>
	<b>P 01-Pi-MKII (oB)</b>	Dito, without bracket	<u>C3</u>

### Pan Speaker – P 02-Pi MKII Series



	<b>P 02-Pi MKII</b>	2-way passive compact loudspeaker with design aluminium housing, Drivers: 2 x high power LF 3.5" and 1x HF of 0.5" coax, Power handling: 100 watt (program), 150 watt (peak), 8 ohm, Connections: 2 x two wire connector, delivery incl. U-bracket	<u>C3</u>
	<b>P 02-Pi MKII (oB)</b>	Dito, without bracket	<u>C3</u>

### Pan Speaker – P 04-Pi MKII Series


	<b>P 04-Pi MKII</b>	compact passive column speaker with design aluminium housing, Drivers: High power 4 x 3.5" , power handling: 200 watt (program), 300 watt (peak), 8 ohm, connections: 2 x two wire connector	<u>C3</u>
	<b>P 04-Pi-100V MKII</b>	compact passive column speaker with design aluminium housing, Drivers: High power 4 x 3.5" , Power: 2.5/5/10/20 watt (100V), connections: 2 x two wire connector	<u>C3</u>
	<b>P 04-Pi-IP65 MKII</b>	compact passive column speaker with design aluminium housing, Drivers: High power 4 x 3.5" , power handling: 200 watt (program), 300 watt (peak), 8 ohm, connections: cable gland and 3m connection cable	<u>C3</u>
	<b>P 04-Pi-IP65-100V MKII</b>	compact passive column speaker with design aluminium housing, Drivers: High power 4 x 3.5" , Power: 2.5/5/10/20 W (100V), connections: cable gland and 3m connection cable	<u>C3</u>
	<b>P 04-EN54 MKII</b>	Dito P 04-Pi-100V MKII but EN-54-24 certified Connections: 1 x 2-pol ceramic block	 <u>C3</u>

\* available Q4/2018

## Pan Speaker – P 08-Pi MKII Series



	<b>P 08-Pi MKII</b>	compact passive column speaker with design aluminium housing, Drivers: High power 8 x 3.5" , power handling: 400 watt (program), 600 watt (peak), 8 ohm, connections: 2 x two wire connector	<u>C3</u>	
	<b>P 08-Pi-100V</b>	compact passive column speaker with design aluminium housing, Drivers: High power 8 x 3.5" , Power: 10/20/40/80 W (100V), connections: 5m 5-wire connector	<u>C3</u>	
	<b>P 08-Pi-IP65 MKII</b>	compact passive column speaker with design aluminium housing, Drivers: High power 8 x 3.5" , power handling: 400 watt (program), 600 watt (peak), 8 ohm, connections: cable gland and 5m connection cable	<u>C3</u>	
	<b>P 08-Pi-IP65-100V MKII</b>	compact passive column speaker with design aluminium housing, Drivers: High power 8 x 3.5" , Power: 5/10/20/40 W W (100V), connections: cable gland and 5m 5-wire connection cable	<u>C3</u>	
	<b>P 08-R MKII</b>	compact passive column speaker with design aluminium housing, Drivers: High power 8 x 3.5" , power handling: 400 watt (program), 600 watt (peak), 8 ohm, 2x NL4 connector, singal switcher for signal routing (NL 1+- / 2+-), <b>standard colour: RAL 9005 black</b>	<u>C3</u>	
	<b>P 08-EN54</b>	Dito P 08-Pi-100V MKII, but EN-54-24 certified Connections: 1 x 2-pol ceramic block		<u>C3</u>

## Pan Speaker – P 8-15-Pi MKII Series



	<b>P 8-15-Pi MKII</b>	compact passive column speaker with design aluminium housing, Drivers: High power 16 x 2.1" , power handling: 200 watt (program), 300 watt (peak), 8 ohm, connections: 2 x two wire connector	<u>C3</u>	
	<b>P 8-15-Pi-100V/80W MKII</b>	compact passive column speaker with design aluminium housing, Drivers: High power 16 x 2.1" , Power: 10/20/40/80 W (100V), connections: 5m 5-wire connector	<u>C3</u>	
	<b>P 8-15-Pi-IP65 MKII</b>	compact passive column speaker with design aluminium housing, Drivers: High power 16 x 2.1" , power handling: 200 watt (program), 300 watt (peak), 8 ohm, connections: cable gland and 5m connection cable	<u>C3</u>	
	<b>P 8-15-Pi-IP65-100V MKII</b>	compact passive column speaker with design aluminium housing, Drivers: High power 16 x 2.1" , Power: 10/20/40/80 W (100V), connections: cable gland and 5m 5-wire connection cable	<u>C3</u>	
	<b>P 8-15-R MKII</b>	compact passive column speaker with design aluminium housing, Drivers: High power 16 x 2.1" , power handling: 200 watt (program), 300 watt (peak), 8 ohm, 2x NL4 connector, singal switcher for signal routing (NL 1+- / 2+-)	<u>C3</u>	

\*\* available Q3


## Pan Speaker – AMT Series

	<p><b>P 161-AMT</b></p> <p>2-way passive compact loudspeaker with design aluminium housing, Drivers: 1 x 6,5" LF driver and 1 x Mundorf AMT HF driver, Power handling: xx watt (program), xx watt (peak), x ohm, Connections: 2 x two wire connector <b>standard colour: RAL 9005 black</b></p>	<p><u>C3</u></p>	
	<p><b>P 261 AMT</b></p> <p>2-way passive compact loudspeaker with design aluminium housing, Drivers: 2 x 6,5" LF driver and 1 x Mundorf AMT HF driver, Power handling: xx watt (program), xx watt (peak), x ohm, connectors: 2 x NL4 <b>standard colour: RAL 9005 black</b></p>	<p><u>C3</u></p>	





## Pan Speaker – Subwoofer Series








	<p><b>P S-208 MKII</b></p> <p>double 8" band-pass passive subwoofer, frequency response: 42 Hz to 120 Hz, power handling: 600 watt (program), 800 watt (peak), 8 Ohm, housing: multi-laminate birch ply construction, connectors: 2 x NL4, selector switch for signal mapping 1 +/- or 2 +/-, <b>standard colour: RAL 9005 black / textured finish</b></p>	<p><u>C3</u></p>	
	<p><b>P S-118</b></p> <p>Single 18" passiv subwoofer, frequency range: 35 Hz to 130 Hz, power handling: 1000 watt (program), 2000 watt (peak), 8 Ohm, multi-laminate birch ply construction, connectors: 2 x NL4, <b>standard colour: RAL 9005 black / textured finish</b></p>	<p><u>C3</u></p>	



## Colour option (RAL-XXXX, powder coated, three gloss levels)

	The painting refers to housing and grids in the same colour, different colours (housing, grid) are available on request.		
	<b>CO 01</b>	Colour option RAL-xxxx for Px 01-x	<u>C3</u>
	<b>CO 02</b>	Colour option RAL-xxxx for Px 02-x	<u>C3</u>
	<b>CO 04</b>	Colour option RAL-xxxx for Px 04-x	<u>C3</u>
	<b>CO 08</b>	Colour option RAL-xxxx for Px 08-x	<u>C3</u>
	<b>CO 161</b>	Colour option RAL-xxxx for P 161-x	<u>C3</u>
	<b>CO 261</b>	Colour option RAL-xxxx for P 261-x	<u>C3</u>
	<b>CO wall mount</b>	Colour option RAL-xxxx for wall mount (without screws)	<u>C3</u>
	<b>CO subwoofer</b>	Colour option RAL-xxxx for subwoofer	<u>C3</u>
	Default colour for all Pan Beam products is aluminium RAL 9006, or RAL-9010 (white) or RAL-9005 (black), unless an other colour information is specified for a product. Usually all products are powdered. Colour have to choose by order, with RAL xxxx (4-bit code) and gloss level. Other colour systems are possible, like RAL (3-bit code), NCS, Pantone, DB etc, on request.		

## Accessories

	<b>wall mount, fix, PB xx MKII</b>	Wall-mount kit for mounting Pan Column-Speaker on wall, PB 04, PB 08, P 04-Pi, P 08-Pi, P 8-15-Pi. (Art. 801839)	<u>C3</u>
	<b>wall mount, turnable, PB xx, MKII</b>	Swivel wall-mount kit for mounting Pan Column-Speaker on Wall (bottom and top) P 04-Pi, P 08-Pi, P 8-15-Pi, PB 04, PB 08 in stainless Steel. (Art. 801840)	<u>C3</u>
	<b>wall mount, horizontal turnable, PB xx (TWM III)</b>	Wall-mount horizontal turnable kit for mounting Pan Column-Speaker on wall, PB 04, PB 08, P 04-Pi, P 08-Pi, P 8-15-Pi. 2 pcs for: PB 16, PB 24. (Art. 801841)	<u>C3</u>
	<b>stand holder MKII, PB xx</b>	Stand mount (35mm), stainless steel for: P 01-Pi, P 02-Pi, P 04-Pi, P 08-Pi, P 8-15-Pi, PB 04, PB 08, PB 16. (Art. 801843)	<u>C3</u>
	<b>slider set, PB xx MKII</b>	Slider set, consist of 2 x PB xx slider, to connect two P 08-Pi together (Art. 801924)	<u>C3</u>
	<b>wall mount, tiltable, turnable (black)</b>	Universal wall mount (horizontal 180° and vertical 0-15° adjustment), up to 10 kg load, incl. Sliding block, <b>standard colour: black</b> (Art. 801449)	<u>C3</u>
	<b>wall mount, tiltable, turnable (white)</b>	Universal wall mount (horizontal 180° and vertical 0-15° adjustment), up to 10 kg load, incl. Sliding block, <b>standard colour: white</b> (art. 801450)	<u>C3</u>
	<b>Rain Hood Px 208</b>	Weather protection fabric for outdoor use. Suitable for bass speakers: PB S-208 and P S-208	<u>C3</u>
	<b>Rain Hood Px 118</b>	Weather protection fabric for outdoor use. Suitable for bass speakers: PB S-118 and P S-118	<u>C3</u>

	<p><b>pole mount PBxx</b></p> <p>Mounting bracket for P/PB 08, PB 16, on poles (art. 802370), stainless steel. Note: Tension straps for attaching to the mast are not included in the bracket.</p>	<u>C3</u>	
	<p><b>Speaker tilt connector „RingLock“</b></p> <p>For speaker stands with tube diameter of 35 mm. A unique patented expanding mandrel system provides a tight and firm fit for the speaker. The moveable plastic splints separate the speaker from the stand creating a vibration-free connection. Easy to use ring lock. Colour black (art. 802349).</p>	<u>C3</u>	
	<p><b>speaker stand with plate RingLock (black)</b></p> <p>speaker stand with patented expanding mandrel system that provides a stable, tight and firm fit for speakers. Connecting the speaker is easy and is done using the handy ring lock - which is simply placed in position and screwed on. Heavy cast iron plate with a relatively small diameter. The tried-and-tested spring-loaded bolt with locking screw makes height adjustment easy and safe. Max. height 1.800 mm, suitable for speakers with max. 20 kg. <b>standard colour: black</b> (art. 801488)</p>	<u>C3</u>	
	<p><b>speaker stand with plate (white)</b></p> <p>A decorative space saving speaker stand. The heavy cast iron plate with a relatively small diameter requires little space. The tried-and-tested spring-loaded bolt with locking screw makes height adjustment easy and safe. The stand has a maximum pull-out height of 1800 mm and is suitable for speakers with a maximum weight of 20 kg. The integrated mounting aid simplifies mounting the loud speaker cabinets. <b>standard colour: white</b> (art. 801580)</p>	<u>C3</u>	
	<p><b>speaker stand with plate (black)</b></p> <p>A decorative space saving speaker stand. The heavy cast iron plate with a relatively small diameter requires little space. The tried-and-tested spring-loaded bolt with locking screw makes height adjustment easy and safe. The stand has a maximum pull-out height of 1800 mm and is suitable for speakers with a maximum weight of 20 kg. The integrated mounting aid simplifies mounting the loud speaker cabinets. <b>standard colour: black</b> (art. 801581)</p>	<u>C3</u>	
	<p><b>ceiling mount, fix, (black) PB xx</b></p> <p>Robust and useful loudspeaker ceiling mount with 250 mm distance and internal cable management. The swivel area is +/- 45 °. Within the parameters - the settings range from 0 to 45°. Max. load is 25kg. The clamping bracket is for loudspeakers with a vertical mounting template from 70 to 76.2 mm. For other attachment possibilities additional adapter brackets are available. A mounting bracket with side and central cable management makes mounting to the ceiling easier. incl. slider block, standard colour: black (art. 801451)</p>	<u>C3</u>	
	<p><b>Ceiling mount, fix, (white) PB xx</b></p> <p>Dito ceiling mount, fix, (black) PB xx but <b>white</b> (art. 801452)</p>	<u>C3</u>	

	<p><b>Telescop ceiling mount, flex, (black) PB xx</b></p> <p>Flexible ceiling mount with variable length 700-1200mm incl. slider block, standard colour: black (art. 802406)</p>	<p><u>C3</u></p>	
	<p><b>Telescop ceiling mount, flex, (white) PB xx</b></p> <p>Flexible ceiling mount with variable length 700-1200mm incl. slider block, standard colour: white (art. 801285)</p>	<p><u>C3</u></p>	

**Ersetzt alle bisherigen Preislisten.  
Remplace tous les listes de prix anciennes.**

**Artikel mit grau unterlegtem Händlercode sind Neuheiten oder haben eine Preisänderung erfahren.**

**Articles avec code client gris sont des nouveautés ou ont changé de prix.**

**Bei Artikeln mit unterstrichenem Händlercode bitte Verfügbarkeit anfragen!  
Articles avec code client souligné demandez leur disponibilité!**