



Line Array Systems	WPM / WPC / WPS	<a href="#">Link</a>
Torus Line Array Systems	T1215 / T1230 / T820	<a href="#">Link</a>
	Zubehör zu T12xx / T820	<a href="#">Link</a>
FlexPoint	2-Weg System ab 4" bis 15", (passiv)	<a href="#">Link</a>
TH Series	THH / THV / THS	<a href="#">Link</a>
Subwoofers	passiv	<a href="#">Link</a>
	aktiv	<a href="#">Link</a>
Stage Monitors	LE100 / LE200 / XE300 / XE500	<a href="#">Link</a>
BlacklineX / XP Series (passiv, aktiv)	2-Weg System ab 8" bis 15", (passiv)	<a href="#">Link</a>
	2-Weg System ab 12", 15", (aktiv)	<a href="#">Link</a>
	Zubehör	<a href="#">Link</a>
O-Line (Line Array Installation)	LineArray	<a href="#">Link</a>
CDD Series (passiv, aktiv)	2-way System ab 5.25" bis 15", schwarz/weiss (passiv)	<a href="#">Link</a>
	Zubehör zu CDD Serie	<a href="#">Link</a>
	DSP und Dante 8", 12", 15", schwarz/weiss (aktiv)	<a href="#">Link</a>
Adorn Series	2-way System 4" und 5", schwarz/weiss	<a href="#">Link</a>
Ceiling Series	Deckenlautsprecher	<a href="#">Link</a>
Amplifiers	iKON Serie / VIA	<a href="#">Link</a>
Controllers	DX-Serie	<a href="#">Link</a>

\* GoWild (kein BOSE) Artikel

## Wavefront Precision Series






	<b>WPM</b>	2-way, passive line array element, LF: 2x6.5" / HF: 3x1.4", 16Ohm, frequency response 76Hz-18kHz +/- 3dB, max. SPL 130dB, 100° hor. / 10° vert, side pocket handles, rear grip handles, (W)500mm x (H)185mm x (D)377mm, 14Kg	<u>C3</u>	3'430.-
	<b>WPM-W</b>	Dito, white	<u>C3</u>	3'430.-
	<b>WPS</b>	3-way, passive line array element, LF: 2x8" / MF: 4x4" / HF: 4x1", 6Ohm, frequency response 70Hz-18kHz +/- 3dB, max. SPL 133dB, 100° hor. / 10° vert, side pocket handles, rear grip handles, (W)650mm x (H)261mm x (D)400mm, 27Kg	<u>C3</u>	4'885.-
	<b>WPS-W</b>	Dito, white	<u>C3</u>	4'885.-
	<b>WPC</b>	3-way, bi-amp line array element, LF: 2x10" / MF: 2x5" / HF: 4x0.7", 8Ohm, frequency response 65Hz-18kHz +/- 3dB, max. SPL 135dB, 100° hor. / 10° vert, side pocket handles, rear grip handles, (W)772mm x (H)319mm x (D)421mm, 35Kg	<u>C3</u>	6'270.-
	<b>WPC-W</b>	Dito, white	<u>C3</u>	6'270.-
	<b>WPL</b>	3-way, bi-amp line array element, LF: 2x12" / MF: 2x6.5" / HF: 3x1", 8Ohm, frequency response 52Hz-18kHz +/- 3dB, max. SPL LF: 135dB / MF: 140dB / HF: 145dB, 90° hor. / 7.5° vert, side pocket handles, (W)1136mm x (H)371mm x (D)526mm, 64Kg	<u>C3</u>	11'880.-

Diverses Zubehör wie: Tour/Install Flybar, Dolly System, Transition Frame etc. auf Anfrage!

<b>Torus</b>				
	<b>T820</b>	2-way, passive, 20° fixed angle array cabinet, LF: 8" / HF: 2x1", 200W AES @80hm, frequency response 70Hz-18kHz +/- 3dB, max. SPL 126dB, 120° hor. / 20° vert, (W)500mm x (H)257mm x (D)320mm, 14Kg	<u>C3</u>	2'640.-
	<b>T1215</b>	2-way, passive, 15° fixed angle array cabinet, LF: 12" / HF: 3x1", 400W AES @80hm, frequency response 65Hz-18kHz +/- 3dB, max. SPL 134dB, 60/75/90° hor. / 15° vert, (W)650mm x (H)369mm x (D)452mm, 31Kg	<u>C3</u>	4'290.-
	<b>T1230</b>	2-way, passive, 30° fixed angle array cabinet, LF: 12" / HF: 3x1", 400W AES @80hm, frequency response 65Hz +/- 3dB, max. SPL 132dB, 60/75/90° hor. / 30° vert, (W)650mm x (H)350mm x (D)442mm, 26Kg	<u>C3</u>	4'290.-
<b>Torus - Accessories</b>				
	<b>POLERIG20</b>	Pole-mount bracket for T8xx cabinets	<u>C3</u>	495.-
	<b>POLERIG1530</b>	Pole-mount bracket for T12xx cabinets	<u>C3</u>	530.-
	<b>SBAR40</b>	Flying Bracket for up to two T8xx or a single T12xx	<u>C3</u>	265.-
	<b>HRIG100</b>	Modular flying bar for horizontal arrays, maximum 3x T8xx or 3x T12xx	<u>C3</u>	660.-
	<b>GSRIG20</b>	Ground-stack frame for T8xx cabinets to SXCF115	<u>C3</u>	1'055.-
	<b>GSRIG1530</b>	Dito, for T12xx cabinets to SXCF118	<u>C3</u>	1'715.-
	<b>T8GRID</b>	Flying frame for 6x T8xx arrays and transition frame for SXCF115 to T8xx array	<u>C3</u>	3'300.-
	<b>T12GRID</b>	Flying frame for T12xx arrays	<u>C3</u>	3'960.-
	<b>T12TRIG</b>	Transition frame for SXCF118 to T12xx array	<u>C3</u>	2'310.-
	<b>T8PB</b>	Simple rigging bar for T8 cabinet, up to 6x T8xx	<u>C3</u>	990.-
	<b>T12PB</b>	Simple rigging bar for T12 cabinet	<u>C3</u>	1'055.-
	<b>ASF20071</b>	Wind-up telescopic pole for T8xx and T12xx cabinet	<u>C3</u>	295.-

Lautsprecher sowie Zubehör auch in weiss erhältlich!


## FlexPoint

	FP4	2-way, passive, coaxial, miniature point source loudspeaker, LF: 4" / HF: 1.25", 60W AES @16Ohm, frequency response 142Hz-18kHz +/- 3dB, max. SPL 102dB, 110° conical, M6 inserts, (W)130mm x (H)130mm x (D)126mm, 1.9Kg	<u>C3</u>	595.-
	FP6	2-way, passive, coaxial, compact point source loudspeaker, LF: 6" / HF: 1.75", 150W AES @16Ohm, frequency response 73Hz-20kHz +/- 3dB, max. SPL 113dB, 100° hor. / 80° vert (user-rotatable), M10 / M6 inserts, (W)321mm x (H)220mm x (D)197mm, 5.5Kg	<u>C3</u>	1'055.-
	FP8	2-way, passive, coaxial, compact point source loudspeaker, LF: 8" / HF: 2", 250W AES @8Ohm, frequency response 63Hz-18kHz +/- 3dB, max. SPL 118dB, 90° hor. / 70° vert (user-rotatable), M10 / M6 inserts, (W)376mm x (H)280mm x (D)265mm, 9.3Kg	<u>C3</u>	1'715.-
	FP12	2-way, passive, coaxial, compact point source loudspeaker, LF: 12" / HF: 3", 350W AES @8Ohm, frequency response 55Hz-20kHz +/- 3dB, max. SPL 122dB, 90° hor. / 60° vert (user-rotatable), M10 / M6 inserts, (W)521mm x (H)390mm x (D)346mm, 17.5Kg	<u>C3</u>	2'640.-
	FP15	2-way, passive, coaxial, compact point source loudspeaker, LF: 15" / HF: 3.5", 500W AES @8Ohm, frequency response 50Hz-20kHz +/- 3dB, max. SPL 126dB, 80° hor. / 50° vert (user-rotatable), M10 / M8 inserts, (W)601mm x (H)460mm x (D)420mm, 27.4Kg	<u>C3</u>	3'300.-




## FlexPoint - Accessories

	FP4Y-B	FP4 Touring & Install Yoke	<u>C3</u>	65.-
	FP6YLT-B	FP6 Landscape Touring Yoke	<u>C3</u>	330.-
	FP8YLT-B	Dito, FP8	<u>C3</u>	395.-
	FP12YLT-B	Dito, FP12	<u>C3</u>	460.-
	FP15YLT-B	Dito, FP15	<u>C3</u>	595.-
	FP6YPT-B	FP6 Portrait Touring Yoke	<u>C3</u>	330.-
	FP8YPT-B	Dito, FP8	<u>C3</u>	395.-
	FP12YPT-B	Dito, FP12	<u>C3</u>	460.-
	FP15YPT-B	Dito, FP15	<u>C3</u>	595.-
	FP6YLI-B	FP6 Landscape Install Yoke	<u>C3</u>	265.-
	FP8YLI-B	Dito, FP8	<u>C3</u>	330.-
	FP12YLI-B	Dito, FP12	<u>C3</u>	395.-
	FP15YLI-B	Dito, FP15	<u>C3</u>	530.-
	FP6YPI-B	FP6 Portrait Install Yoke	<u>C3</u>	265.-
	FP8YPI-B	Dito, FP8	<u>C3</u>	330.-
	FP12YPI-B	Dito, FP12	<u>C3</u>	395.-
	FP15YPI-B	Dito, FP15	<u>C3</u>	530.-





## O-Line 4 Pack

	<b>O-Line</b>	<p>2 x 3.5" scalable, 2-way, micro-line array, 4 cabinet array (Picture: 2 x Omniline 4 pack - price per 4-pack!) Tech. spec. per module: 50W AES, 200W peak, 84-92 dB 1W/1m, 100° hor., 5° vert., 16Ω, light grey,</p> <p>Tech. spec. per 4 pack: 200W AES, 800W peak, 96dB 1W/1m, 4Ω, 14.4kg</p>	<u>C3</u>	2'840.-
---	---------------	--	-----------	---------





## Accessories

	<b>ASF20023</b>	Flying Bracket	<u>C3</u>	460.-
	<b>ASF20021</b>	Wall Bracket for 1 x 4-Pack O-Line Array	<u>C3</u>	530.-
	<b>ASF20022</b>	Wall Bracket for 2-3 x 4-Pack O-Line Arrays	<u>C3</u>	1'055.-




## TH Series

	<b>THH</b>	<p>3-way, bi-amp trapezoid hybrid fully horn loaded, LF: 15" / MF: 10" / HF: 1", LF: 750W AES @80hm, MF+HF: 300W AES @80hm, frequency response 50Hz-18kHz +/- 3dB, max. SPL 133dB, 70° hor. / 40° vert, pocket handle, M10 inserts, (W)1067mm x (H)558mm x (D)780mm, 77Kg</p>	<u>C3</u>	5'940.-
	<b>THV</b>	Dito, Vertical	<u>C3</u>	5'940.-
	<b>THS</b>	<p>3-way, bi-amp triaxial point source loudspeaker, LF: 15" / MF: 1.4" / HF: 1.4", LF: 800W AES @80hm, MF+HF: 110W AES @80hm, frequency response 54Hz-18kHz +/- 3dB, max. SPL 129dB, 85° hor. / 50° vert, pocket handle, M10 inserts, (W)511mm x (H)710mm x (D)511mm, 35.6Kg</p>	<u>C3</u>	4'620.-
	<b>THSYLT-B</b>	Landscape Touring Yoke	<u>C3</u>	660.-
	<b>THSYLI-B</b>	Landscape Install Yoke	<u>C3</u>	595.-
	<b>THSYPT-B</b>	Portrait Touring Yoke	<u>C3</u>	725.-
	<b>THSYPI-B</b>	Portrait Install Yoke	<u>C3</u>	595.-










## Stage Monitors

	<b>LE100</b>	2-way, passive coaxial differential dispersion, LF: 12" / HF: 1", 300W AES @8Ohm, frequency response 78Hz-20kHz +/- 3dB, max. SPL 129dB, 110° hor. / 60° vert, pocket handle, M8 inserts, pole mounting, protective rubber feet (W)490mm x (H)302mm x (D)472mm, 18Kg	<u>C3</u>	1'980.-
	<b>LE200</b>	2-way, passive coaxial differential dispersion, LF: 15" / HF: 1.4", 400W AES @8Ohm, frequency response 78Hz-20kHz +/- 3dB, max. SPL 133dB, 110° hor. / 60° vert, pocket handle, M8 inserts, pole mounting, protective rubber feet (W)610mm x (H)364mm x (D)562mm, 26Kg	<u>C3</u>	2'375.-
	<b>XE300</b>	2-way, passive/bi-amp coaxial differential dispersion, LF: 12" / HF: 1.4", LF: 350W AES @6Ohm, HF: 80W AES @8Ohm, frequency response 67Hz-18kHz +/- 3dB, max. SPL 139dB, 60° hor. / 90° vert, pocket handle, M8 inserts, protective rubber feet, (W)550mm x (H)290mm x (D)470mm, 19Kg	<u>C3</u>	3'300.-
	<b>XE500</b>	2-way, passive/bi-amp coaxial differential dispersion, LF: 15" / HF: 1.4", LF: 550W AES @4Ohm, HF: 80W AES @8Ohm, frequency response 62Hz-18kHz +/- 3dB, max. SPL 143dB, 60° hor. / 70° vert, bar handles, M8 inserts, protective rubber feet, (W)635mm x (H)364mm x (D)583mm, 19Kg	<u>C3</u>	4'355.-

## CDD Live – aktiv

	<b>CDD-LIVE8B</b>	2-way, powered ultra-compact coaxial differential dispersion system, LF: 8" / HF: 1", peak 1300W, continuous 650W, frequency response 70Hz-20kHz +/- 3dB, max. SPL 123dB, 110° hor. / 60° vert, (user-rotatable), pocket handle, M8 inserts, pole mounting, (W)258mm x (H)428mm x (D)254mm, 14Kg, Dante, DSP	<u>C3</u>	2'905.-
	<b>CDD-LIVE8W</b>	Dito, white	<u>C3</u>	2'905.-
	<b>CDD-LIVE12B</b>	2-way, powered ultra-compact coaxial differential dispersion system, LF: 12" / HF: 1", peak 2500W, continuous 1250W, frequency response 62Hz-20kHz +/- 3dB, max. SPL 128dB, 110° hor. / 60° vert, (user-rotatable), pocket handle, M8 inserts, pole mounting, (W)359mm x (H)580mm x (D)373mm, 28Kg, Dante, DSP	<u>C3</u>	3'695.-
	<b>CDD-LIVE12W</b>	Dito, white	<u>C3</u>	3'695.-
	<b>CDD-LIVE15B</b>	2-way, powered ultra-compact coaxial differential dispersion system, LF: 15" / HF: 1.4", peak 2500W, continuous 1250W, frequency response 55Hz-20kHz +/- 3dB, max. SPL 132dB, 110° hor. / 60° vert, (user-rotatable), pocket handle, M8 inserts, pole mounting, (W)427mm x (H)696mm x (D)422mm, 37Kg, Dante, DSP	<u>C3</u>	4'620.-
	<b>CDD-LIVE15W</b>	Dito, white	<u>C3</u>	4'620.-

## CDD Live – Accessories


	<b>CDDCB6/8B</b>	Ceiling bracket for CDD-Live 8, black	C3	200.–
	<b>CDDCB6/8W</b>	Dito, white	C3	200.–
	<b>WB6/8B</b>	Wall bracket for CDD-Live 8, black, weatherised	C3	75.–
	<b>WB6/8W</b>	Dito, white	C3	75.–
	<b>WB10/12B</b>	Wall bracket for CDD-Live 12, black, weatherised	C3	85.–
	<b>WB10/12W</b>	Dito, white	C3	85.–
	<b>CDDLUB8B</b>	Universal bracket for CDD-Live 8, black	<u>C3</u>	330.–
	<b>ASF20046</b>	Universal bracket for CDD-Live 12, black	<u>C3</u>	595.–
	<b>ASF20048</b>	Universal bracket for CDD-Live 15, black	<u>C3</u>	595.–
	<b>CDDL YA8B</b>	Yoke assembly for CDD-Live 8, black	<u>C3</u>	330.–
	<b>CDDL YA8W</b>	Dito, white	<u>C3</u>	330.–
	<b>CDDL YA12B</b>	Yoke assembly for CDD-Live 12, black	<u>C3</u>	345.–
	<b>CDDL YA12W</b>	Dito, white	<u>C3</u>	345.–
	<b>CDDL YA15B</b>	Yoke assembly for CDD-Live 15, black	<u>C3</u>	395.–
	<b>CDDL YA15W</b>	Dito, white	<u>C3</u>	395.–
	<b>HTKCT05</b>	8mm shouldered eye bolt for CDD-Live 8, 12, 15	<u>C3</u>	40.– (Stück)
	<b>ASF20045</b>	Universal 35mm pole mount adaptor	<u>C3</u>	65.–
	<b>ASF20071</b>	Wind-up telescopic pole	<u>C3</u>	295.–

Diverses Zubehör wie: Transit Cover, Rain Kit Upgrade auf Anfrage!



## CDD Series – passiv







VPE

	<b>CDD5B</b>	2-way, passive ultra compact differential dispersion system, nLF: 5.25" / HF: 0.75", 100W AES @80hm, frequency response 100Hz-20kHz +/- 3dB, max. SPL 116dB, 120° hor. / 80° vert, (user-rotatable), M6 inserts, (W)160mm x (H)230mm x (D)149mm, 3Kg, incl. wall bracket	2	C3	275.–
	<b>CDD5W</b>	Dito, white	2	C3	275.–
	<b>CDD5BTX-WR</b>	Dito, 6/12.5/25W@100V, black, weatherised	2	C3	335.–
	<b>CDD5WTX-WR</b>	Dito, 6/12.5/25W@100V, white, weatherised	2	C3	335.–
	<b>CDD5BTX-MAR</b>	For cruise ships and seaside resort applications, black	2	<u>C3</u>	475.–
	<b>CDD5WTX-MAR</b>	Dito, white	2	<u>C3</u>	475.–
	<b>CDD6B</b>	2-way, passive ultra compact differential dispersion system, LF: 6.5" / HF: 1", 150W AES @80hm, frequency response 80Hz-20kHz +/- 3dB, max. SPL 119dB, 110° hor. / 80° vert, (user-rotatable), M6 inserts, (W)210mm x (H)325mm x (D)210mm, 5.7Kg	2	C3	460.–
	<b>CDD6W</b>	Dito, white	2	C3	460.–
	<b>CDD6BTX-WR</b>	Dito, 12.5/25/50W@100V, black, weatherised	2	C3	530.–
	<b>CDD6WTX-WR</b>	Dito, 12.5/25/50W@100V, white, weatherised	2	C3	530.–
	<b>CDD6BTX-MAR</b>	For cruise ships and seaside resort applications, black	2	<u>C3</u>	740.–
	<b>CDD6WTX-MAR</b>	Dito, white	2	<u>C3</u>	740.–
	<b>CDD8B</b>	2-way, passive ultra compact differential dispersion system, LF: 8" / HF: 1", 200W AES @80hm, frequency response 70Hz-20kHz +/- 3dB, max. SPL 119dB, 110° hor. / 60° vert, (user-rotatable), M6 inserts, (W)256mm x (H)410mm x (D)252mm, 9.5Kg		C3	890.–
	<b>CDD8W</b>	Dito, white		C3	890.–
	<b>CDD8B-WR</b>	Dito, black, weatherised		<u>C3</u>	1'100.–
	<b>CDD8W-WR</b>	Dito, white, weatherised		<u>C3</u>	1'100.–
	<b>CDD8BTX</b>	Dito, 15/30/60/120W@100V, 11.1Kg, black		<u>C3</u>	1'025.–
	<b>CDD8WTX</b>	Dito, white		<u>C3</u>	1'025.–
	<b>CDD8BTX-WR</b>	Dito, black, weatherised		<u>C3</u>	1'220.–
	<b>CDD8WTX-WR</b>	Dito, white, weatherised		<u>C3</u>	1'220.–
	<b>CDD8BTX-MAR</b>	For cruise ships and seaside resort applications, black		<u>C3</u>	1'520.–
<b>CDD8WTX-MAR</b>	Dito, white		<u>C3</u>	1'520.–	







	<b>CDD10B</b>	2-way, passive ultra compact differential dispersion system, LF: 10" / HF: 1", 250W AES @8Ohm, frequency response 65Hz-20kHz +/- 3dB, max. SPL 126dB, 110° hor. / 60° vert (user-rotatable), M6 inserts, (W)323mm x (H)513mm x (D)310mm, 15.3Kg	C3	1'320.-
	<b>CDD10W</b>	Dito, white	C3	1'320.-
	<b>CDD10B-WR</b>	Dito, black, weatherised	C3	1'650.-
	<b>CDD10W-WR</b>	Dito, white, weatherised	C3	1'650.-
	<b>CDD10BTX</b>	Dito, 15/30/60/120W@100V, 16.9Kg, black	C3	1'520.-
	<b>CDD10WTX</b>	Dito, white	C3	1'520.-
	<b>CDD10BTX-WR</b>	Dito, black, weatherised	C3	1'850.-
	<b>CDD10WTX-WR</b>	Dito, white, weatherised	C3	1'850.-
	<b>CDD10BTX-MAR</b>	For cruise ships and seaside resort applications, black	C3	2'375.-
	<b>CDD10WTX-MAR</b>	Dito, white	C3	2'375.-
	<b>CDD12B</b>	2-way, passive ultra compact differential dispersion system, LF: 12" / HF: 1", 300W AES @8Ohm, frequency response 62Hz-20kHz +/- 3dB, max. SPL 128dB, 110° hor. / 60° vert (user-rotatable), M8 inserts, (W)360mm x (H)560mm x (D)350mm, 19Kg	C3	1'915.-
	<b>CDD12W</b>	Dito, white	C3	1'915.-
	<b>CDD12B-WR</b>	Dito, black, weatherised	C3	2'180.-
	<b>CDD12W-WR</b>	Dito, white, weatherised	C3	2'180.-
	<b>CDD12B-MAR</b>	For cruise ships and seaside resort applications, black	C3	3'035.-
	<b>CDD12W-MAR</b>	Dito, white	C3	3'035.-
	<b>CDD15B</b>	2-way, passive ultra compact differential dispersion system, LF: 15" / HF: 1.4", 400W AES @8Ohm, frequency response 55Hz-18kHz +/- 3dB, max. SPL 132dB, 110° hor. / 60° vert (user-rotatable), M8 inserts, (W)432mm x (H)685mm x (D)413mm, 19Kg	C3	2'375.-
	<b>CDD15W</b>	Dito, white	C3	2'375.-
	<b>CDD15B-WR</b>	Dito, black, weatherised	C3	2'770.-
	<b>CDD15W-WR</b>	Dito, white, weatherised	C3	2'770.-
	<b>CDD15B-MAR</b>	For cruise ships and seaside resort applications, black	C3	3'830.-
	<b>CDD15W-MAR</b>	Dito, white	C3	3'830.-

## CDD Series - Accessories

	<b>WB6/8B</b>	Wall bracket for CDD6Bxx – CDD8Bxx, black, weatherised	C3	75.–
	<b>WB6/8W</b>	Dito, white	C3	75.–
	<b>WB6/8B-MAR</b>	Wall bracket for CDD6BTX-MAR – CDD8BTX-MAR, black	<u>C3</u>	395.–
	<b>WB6/8W-MAR</b>	Dito white	<u>C3</u>	395.–
	<b>WB10/12B</b>	Wall bracket for CDD10Bxx – CDD12Bxx, black, weatherised	C3	85.–
	<b>WB10/12W</b>	Dito white	C3	85.–
	<b>WB10/12B-MAR</b>	Wall bracket for CDD10BTX-MAR – CDD12BTX-MAR, black	C3	460.–
	<b>WB10/12W-MAR</b>	Dito white	C3	460.–
	<b>WB15B</b>	Wall bracket for CDD15Bxx, black, weatherised	<u>C3</u>	130.–
	<b>WB15W</b>	Dito white	<u>C3</u>	130.–
	<b>CDDCB5B-WR</b>	Ceiling bracket for CDD5Bxx, black, weatherised	C3	95.–
	<b>CDDCB5W-WR</b>	Dito, white	C3	95.–
	<b>CDDCB6/8B-WR</b>	Ceiling bracket for CDD6Wxx – CDD8Wxx, black, weatherised	C3	200.–
	<b>CDDCW6/8W-WR</b>	Dito, white	C3	200.–
	<b>CDDY10B</b>	Yoke assembly for CDD10Bxx, black, weatherised	C3	330.–
	<b>CDDY10W</b>	Dito, white	C3	330.–
	<b>CDDY12B</b>	Yoke assembly for CDD12Bxx, black, weatherised	C3	395.–
	<b>CDDY12W</b>	Dito, white	C3	395.–
	<b>CDDY15B</b>	Yoke assembly for CDD15Bxx, black, weatherised	C3	430.–
	<b>CDDY15W</b>	Dito, white	C3	430.–
	<b>HTKCT05</b>	8mm shouldered eye bolt for CDD 10, 12, 15	<u>C3</u>	40.– (Stück)

## BlacklineX Series – passiv

	<b>X8B</b>	2-way, passive ultra compact system, LF: 8" / HF: 1", 200W AES @8Ohm, frequency response 70Hz-20kHz +/- 3dB, max. SPL 121dB, 90° hor. / 50° vert (user-rotatable), M6/M8 inserts, pocket handle, pole mounting, (W)257mm x (H)422mm x (D)243mm, 8Kg	C3	530.–
	<b>X10B</b>	2-way, passive ultra compact system, LF: 10" / HF: 1", 250W AES @8Ohm, frequency response 65Hz-20kHz +/- 3dB, max. SPL 124dB, 90° hor. / 50° vert (user-rotatable), M8 inserts, pocket handle, pole mounting, (W)324mm x (H)522mm x (D)289mm, 14Kg	C3	790.–
	<b>X12B</b>	2-way, passive ultra compact system, LF: 12" / HF: 1", 300W AES @8Ohm, frequency response 65Hz-20kHz +/- 3dB, max. SPL 128dB, 80° hor. / 50° vert (user-rotatable), M8 inserts, pocket handle, pole mounting, (W)358mm x (H)574mm x (D)337mm, 17Kg	C3	925.–
	<b>X15B</b>	2-way, passive ultra compact system, LF: 15" / HF: 1", 400W AES @8Ohm, frequency response 55Hz-20kHz +/- 3dB, max. SPL 131dB, 80° hor. / 50° vert (user-rotatable), M8 inserts, pocket handle, pole mounting, (W)427mm x (H)690mm x (D)419mm, 24Kg	C3	1'055.–

## BlacklineXP Series – Powered



	<b>XP12</b>	2-way, powered compact system, LF: 12" / HF: 1", peak 1300W, frequency response 62Hz-20kHz +/- 3dB, max. SPL 128dB, 80° hor. / 50° vert, (user-rotatable), pocket handle, M8 inserts, pole mounting, (W)358mm x (H)574mm x (D)318mm, 18Kg, DSP	C3	1'450.–
	<b>XP15</b>	2-way, powered compact system, LF: 15" / HF: 1", peak 1300W, frequency response 55Hz-20kHz +/- 3dB, max. SPL 131dB, 80° hor. / 50° vert, (user-rotatable), pocket handle, M8 inserts, pole mounting, (W)427mm x (H)690mm x (D)407mm, 26Kg, DSP	C3	1'650.–

## BlacklineX / XP Series – Accessories

	<b>WB6/8B</b>	Wall bracket for X8B, black, weatherised	C3	75.–
	<b>WB10/12B</b>	Wall bracket for X10B - X12B - X15B – XP12, black, weatherised	C3	85.–
	<b>WB15B</b>	Wall bracket for CDD15Bxx, black, weatherised	C3	130.–
	<b>HTKCT04</b>	Pole for BlacklineX	C3	35.–
	<b>HTKCT05</b>	8mm shouldered eye bolt for X8, X10, X12, X15	C3	40.– (Stück)




Adorn – Series			VPE		
	A40B	2-way, passive ultra compact system, LF: 4" / HF: 0.75", 40W AES @16Ohm, frequency response 98Hz-17kHz +/- 3dB, max. SPL 109dB, 110° hor. / 80° vert, (W)124mm x (H)200mm x (D)144mm, 1.7Kg, incl. wall bracket	2	C3	140.–
	A40W	Dito, white	2	C3	140.–
	A40TB	Dito, 2.5/5/10W@100V, 2.1Kg, black	2	C3	170.–
	A40TW	Dito, white	2	C3	170.–
	A55B	2-way, passive ultra compact system, LF: 5.25" / HF: 0.75", 50W AES @16Ohm, frequency response 90Hz-17kHz +/- 3dB, max. SPL 109dB, 110° hor. / 80° vert, (W)152mm x (H)245mm x (D)140mm, 2.1Kg, incl. wall bracket	2	C3	185.–
	A55W	Dito, white	2	C3	185.–
	A55TB	Dito, 7.5/15/30W@100V, 2.8Kg, black	2	C3	225.–
	A55TW	Dito, white	2	C3	225.–
	AIPKIT-B	IP44 Connector cover for A40 and A55 Series, black	2	C3	10.–
	AIPKIT-W	Dito, white	2	C3	10.–
Adorn Series – Accessories					
	CDDCB5B-WR	Ceiling bracket for A40xx – A55xx, black, weatherised		C3	95.–
	CDDCB5W-WR	Dito, white		C3	95.–
Subwoofer – passiv					
	SX110B	slimline, direct radiating subwoofer, 10", 250W AES @8Ohm, frequency response 50Hz-150Hz +/- 3dB, max. SPL 127dB, omnidirectional, M8 inserts, (W)417mm x (H)297mm x (D)415mm, 12Kg		C3	560.–
	SX110W	Dito, white		C3	560.–
	SX210B	slimline, dual-driver direct radiating subwoofer, 2x 10", 500W AES @4Ohm, frequency response 50Hz-150Hz +/- 3dB, max. SPL 133dB, omnidirectional, M8 inserts, bar handles, (W)718mm x (H)295mm x (D)465mm, 20Kg		C3	910.–
	SX210W	Dito, white		C3	910.–
	SX112B	ultra compact, direct radiating subwoofer 12", 400W AES @8Ohm, frequency response 48Hz-150Hz +/- 3dB, max. SPL 132dB, omnidirectional, M10 inserts, (W)487mm x (H)390mm x (D)410mm, 21.5Kg		C3	1'025.–
	SX112W	Dito, white		C3	1'025.–
	SX112-W-MAR	For cruise ships and seaside resort applications, white		C3	2'575.–
	SX212B	compact, dual-driver direct radiating subwoofer 2x 12", 800W AES @4Ohm, frequency response 48Hz-150Hz +/- 3dB, max. SPL 138dB, omnidirectional, M10 inserts, (W)872mm x (H)390mm x (D)437mm, 39Kg		C3	1'385.–
	SX212W	Dito, white		C3	1'385.–

	<b>X115B</b>	compact, direct radiating subwoofer, 15", 500W AES @80hm, frequency response 45Hz-150Hz +/- 3dB, max. SPL 135dB, omnidirectional, M10 inserts, bar handles, pole mounting, provision for castors, (W)465mm x (H)590mm x (D)565mm, 27Kg	<u>C3</u>	1'055.-
	<b>SX115</b>	compact, direct radiating subwoofer, 15", 1000W AES @80hm, frequency response 45Hz-100Hz +/- 3dB, max. SPL 136dB, omnidirectional, bar handles, pole mounting, provision for castors, (W)500mm x (H)451mm x (D)678mm, 36.5Kg	<u>C3</u>	1'980.-
	<b>SX215</b>	compact, dual-driver direct radiating subwoofer, 2x 15", 1600W AES @40hm, frequency response 45Hz-100Hz +/- 3dB, max. SPL 136dB, omnidirectional, provision for castors, (W)961mm x (H)463mm x (D)679mm, 64Kg	<u>C3</u>	2'640.-
	<b>SXC115</b>	compact, cardioid subwoofer, 15" 1000W AES @80hm, 12" 800W AES @80hm, frequency response 44Hz-150Hz +/- 3dB, max. SPL 137dB, cardioid, M10 inserts, bar handles, pole mounting, provision for castors, (W)500mm x (H)550mm x (D)811mm, 53Kg	<u>C3</u>	3'630.-
	<b>SXC115W</b>	Dito, white	<u>C3</u>	3'630.-
	<b>SXCF115</b>	Dito, flown, (W)500mm x (H)552mm x (D)810mm, 61Kg	<u>C3</u>	5'610.-
	<b>X118B</b>	compact, direct radiating subwoofer, 18", 500W AES @80hm, frequency response 42Hz-150Hz +/- 3dB, max. SPL 137dB, omnidirectional, M10 inserts, bar handles, pole mounting, provision for castors, (W)530mm x (H)669mm x (D)640mm, 33Kg	C3	1'320.-
	<b>SX118B</b>	compact, direct radiating subwoofer, 18", 1000W AES @80hm, frequency response 47Hz-150Hz +/- 3dB, max. SPL 138dB, omnidirectional, M10 inserts, bar handles, pole mounting, provision for castors, (W)600mm x (H)509mm x (D)632mm, 43.5Kg	<u>C3</u>	2'640.-
	<b>SX118W</b>	Dito, white	<u>C3</u>	2'640.-
	<b>SX118B-MAR</b>	For cruise ships and seaside resort applications, black	<u>C3</u>	3'960.-
	<b>SX118W-MAR</b>	Dito, white	<u>C3</u>	3'960.-
	<b>SXC118B</b>	compact, cardioid subwoofer, 18" 1000W AES @80hm, 14" 800W AES @80hm, frequency response 43Hz-150Hz +/- 3dB, max. SPL 140dB, cardioid, M10 inserts, bar handles, pole mounting, provision for castors, (W)650mm x (H)603mm x (D)812mm, 73Kg	<u>C3</u>	4'950.-
	<b>SXC118W</b>	Dito, white	<u>C3</u>	4'950.-
	<b>SXCF118B</b>	Dito, flown, (W)650mm x (H)611mm x (D)812mm, 75Kg	<u>C3</u>	6'600.-
	<b>X218</b>	dual-driver direct radiating subwoofer, 2x 18", 1600W AES @40hm, frequency response 42Hz-200Hz +/- 3dB, max. SPL 141dB, omnidirectional, M10 inserts, bar handles, pole mounting, provision for castors, (W)1049mm x (H)587mm x (D)727mm, 88Kg	<u>C3</u>	2'310.-



	<b>SX218B</b>	dual-driver direct radiating subwoofer, 2x 18", 2000W AES @2x 8Ohm, frequency response 35Hz-200Hz +/- 3dB, max. SPL 144dB, omnidirectional, M10 inserts, bar handles, pole mounting, provision for castors, (W)1093mm x (H)537mm x (D)792mm, 102Kg	<u>C3</u>	5'015.-
	<b>SX218W</b>	Dito, white	<u>C3</u>	5'015.-
	<b>SX218B-MAR</b>	For cruise ships and seaside resort applications, black	<u>C3</u>	7'655.-
	<b>SX218W-MAR</b>	Dito, white	<u>C3</u>	7'655.-
	<b>SXH218</b>	hybrid® horn/reflex flown dual-driver subwoofer, 2x 18", 3000W AES @4Ohm, frequency response 32Hz-200Hz +/- 3dB, max. SPL 148dB, omnidirectional, bar handles, (W)1112mm x (H)609mm x (D)1151mm, 116Kg	<u>C3</u>	8'910.-
	<b>SXHF218</b>	Dito, flown, (W)1148mm x (H)604mm x (D)1155mm, 138Kg	<u>C3</u>	11'220.-

Diverses Zubehör wie: Transit Cover, Rain Kit Upgrade auf Anfrage!

## Subwoofer – powerd

	<b>XP118</b>	powerd compact direct radiating subwoofer, 18", peak 2000W, frequency response 52Hz-150Hz +/- 3dB, max. SPL 137dB, omnidirectional, M10 inserts, bar handles, pole mounting, provision for castors, (W)600mm x (H)507mm x (D)632mm, 46.5Kg	<u>C3</u>	1'915.-
	<b>SXP118B</b>	powerd compact direct radiating subwoofer, 18", peak 2000W, frequency response 47Hz-150Hz +/- 3dB, max. SPL 135dB, omnidirectional, M10 inserts, bar handles, pole mounting, provision for castors, (W)662mm x (H)536mm x (D)640mm, 44Kg, Dante, DSP	<u>C3</u>	4'620.-
	<b>SXP118W</b>	Dito, white	<u>C3</u>	4'620.-
	<b>SXP218B</b>	powerd dual-driver compact direct radiating subwoofer, 2x 18", peak 4000W, frequency response 35Hz-150Hz +/- 3dB, max. SPL 143dB, omnidirectional, M10 inserts, bar handles, pole mounting, provision for castors, (W)1085mm x (H)537mm x (D)792mm, 101Kg, Dante, DSP	<u>C3</u>	6'600.-
	<b>SXP218W</b>	Dito, white	<u>C3</u>	6'600.-

## Subwoofer – Accessories

	<b>HTKCT05</b>	8mm shouldered eye bolt for SX110, SX210, X115,	<u>C3</u>	40.- (Stück)
	<b>HTKCT06</b>	10mm shouldered eye bolt for SX112, SX212, SX118, SXC118, SX218, SXP118, SXP218	<u>C3</u>	45.- (Stück)
	<b>ASF20071</b>	Wind-up telescopic pole for SX118, SXC118, SX218, SXP118, SXP218	<u>C3</u>	295.-






Ceiling Series			VPE		
	C4.8T	2-way, passive high performance ceiling system, LF: 4" / HF: 0.8", 40W AES @16Ohm, 3/6/12.5/25W@100V, frequency response 100Hz-20kHz +/- 3dB, max. SPL 108dB, 180° conical, cut out 178mm, Ø 205mm x (D)131mm, 2.6Kg	2	C3	200.-
	C6.8T	2-way, passive high performance ceiling system, LF: 6.5" / HF: 0.8", 75W AES @16Ohm, 5/10/20/40W@100V, frequency response 90Hz-20kHz +/- 3dB, max. SPL 112dB, 180° conical, cut out 224mm, Ø 260mm x (D)181mm, 3.5Kg	2	C3	275.-
	C8.1T	2-way, passive high performance ceiling system, LF: 8" / HF: 1", 125W AES @16Ohm, 7.5/15/30/60W@100V, frequency response 80Hz-18kHz +/- 3dB, max. SPL 116dB, 180° conical, cut out 308mm, Ø 354mm x (D)258mm, 6.7Kg	2	C3	395.-
	ACS-40TS	2-way, passive ultra compact ceiling system, LF: 4" / HF: 0.75", 40W AES @16Ohm, 5/10/20@100V, frequency response 106Hz-20kHz +/- 3dB, max. SPL 108dB, 180° conical, cut out 197mm, Ø 221mm x (D)100mm, 2.2Kg	2	C3	165.-
	ACS-55TS	2-way, passive ultra compact ceiling system, LF: 5.25" / HF: 0.75", 50W AES @16Ohm, 7.5/15/30@100V, frequency response 117Hz-20kHz +/- 3dB, max. SPL 113dB, 180° conical, cut out 222mm, Ø 245mm x (D)100mm, 2.8Kg	2	C3	200.-
	ACS-55T	Dito, (D)209mm, 3Kg	2	C3	225.-
	ACP-55TW	Dito, pendant speaker, white		C3	295.-
	ACP-55TB	Dito, pendant speaker, black		C3	295.-
Accessories					
	GEB-180T150	Einbetoniergehäuse mit Einbauöffnung 180mm, Höhe Innen 150mm, Höhe Aussen 165mm, Gewicht 1'160 Gr. <u>Passend zu:</u> Martin Audio C4.8T	1	C3	75.-
	GEB-200T150	Einbetoniergehäuse mit Einbauöffnung 200mm, Höhe Innen 150mm, Höhe Aussen 165mm, Gewicht 1'160 Gr. <u>Passend zu:</u> Martin Audio ACS-40TS	1	C3	75.-
	GEB-225T180	Einbetoniergehäuse mit Einbauöffnung 225mm, Höhe Innen 180mm, Höhe Aussen 195mm, Gewicht 1'350 Gr. <u>Passend zu:</u> Martin Audio ACS-55TS, Martin Audio C6.8T	1	C3	75.-
	Adorn CK3	3m cable with carabiner	2	C3	35.- (Stück)



## Amplifiers

	<b>iK41 DANTE</b>	4 channel Class D amplifier, 6'000 Watts RMS all channels driven, (1500W per channel @ 2Ω) 96kHz, DSP inputs and outputs, Analogue, AES3, Ethernet, Dante Powercon™, 12.5Kg	<u>C3</u>	7'260.–
	<b>iK42 DANTE</b>	4 channel Class D amplifier, 20'000 Watts RMS all channels driven, (5000W per channel @ 2Ω) 96kHz, DSP inputs and outputs, Analogue, AES3, Ethernet, Dante Powercon™, 12.5Kg	<u>C3</u>	9'700.–
	<b>iK81 DANTE</b>	8 channel Class D amplifier, 10'000 Watts RMS all channels driven (1250W per channel @ 2/4/8Ω) 96kHz, DSP inputs and outputs, Analogue, AES3, Ethernet, Dante Powercon™, 12.5Kg	<u>C3</u>	10'495.–
	<b>VIA2004</b>	Class D, 4x 500W@4Ω, 4x 250W@8Ω, 8Kg	<u>C3</u>	1'320.–
	<b>VIA2502</b>	Class D, 2x 1250W@2Ω, 2x 800W@4Ω, 2x 450W@8Ω, 8Kg	<u>C3</u>	1'980.–
	<b>VIA5002</b>	Class D, 2x 2500W@4Ω, 2x 1600W@8Ω, 10Kg	<u>C3</u>	3'300.–
	<b>VIA5004</b>	Class D, 4x 1250W@2Ω, 4x 800W@4Ω, 4x 450W@8Ω, 10Kg	<u>C3</u>	3'300.–

## Controllers

	<b>DX4.0 DANTE</b>	System Controller, 4In / 8Out, AES3, Dante, 1HE	<u>C3</u>	3'630.–
	<b>DX0.4</b>	System Controller, 2In / 4Out, Ethernet, USB, 1HE	<u>C3</u>	725.–
	<b>DX0.6</b>	System Controller, 2In / 6Out, Ethernet, USB, 1HE	<u>C3</u>	990.–

*Ersetzt alle bisherigen Preislisten.*

*Remplace et annule les précédentes listes de prix.*

*Artikel mit grau unterlegtem Händlercode sind Neuheiten oder haben eine Preisänderung erfahren.*

*Articles avec code client gris sont des nouveautés ou ont changé de prix.*

*Bei Artikeln mit unterstrichenem Händlercode bitte Verfügbarkeit anfragen!*

Preise gültig ab 01.01.2025 • Verkaufspreise in CHF, inkl. 8.1% MWSt. • Preisänderung vorbehalten!  
Prix valables dès le 01.01.2025 • Prix de vente en CHF, 8.1% TVA incluse • Sous réserve de changement de prix!

Seite 16/16  
Page 16/16