



Line Array Systems	MLA / MLA Compact / MLA Mini	<a href="#">Link</a>
	WPM / WPC	<a href="#">Link</a>
	Subwoofer für WPM	<a href="#">Link</a>
Differential Dispersion™ systems	DD12 / DD6 / W8VDQ	<a href="#">Link</a>
	Zubehör zu DDxx / W8VDQ	<a href="#">Link</a>
Wavefront XD Series	XD12 / XD15	<a href="#">Link</a>
	Zubehör zu XDxx	<a href="#">Link</a>
TH Series	THH / THV	<a href="#">Link</a>
Subwoofers	BlacklineX / CSX / SX	<a href="#">Link</a>
Stage Monitors	LE100 / LE200 / XE300 / XE500	<a href="#">Link</a>
BlacklineX Series	2-Weg System ab 8" bis 15", schwarz/weiss	<a href="#">Link</a>
	Subwoofer ab 2x12" bis 18", schwarz/weiss	<a href="#">Link</a>
	Zubehör	<a href="#">Link</a>
O-Line (Line Array Installation)	OmniLine	<a href="#">Link</a>
CDD Series (Installation)	2-way System ab 5.25" bis 15", schwarz/weiss	<a href="#">Link</a>
	Subwoofer ab 10" bis 2x18", schwarz/weiss	<a href="#">Link</a>
	Zubehör zu CDD Serie	<a href="#">Link</a>
	Aktiv mit DSP und Dante 8", 12", 15"	<a href="#">Link</a>
Adorn Series	2-way System 4" und 5" , schwarz/weiss	<a href="#">Link</a>
Ceiling Series	Deckenlautsprecher	<a href="#">Link</a>
Amplifiers	MAxx Serie / iKON Serie / VIA	<a href="#">Link</a>
Controllers	DX-Serie / Merlin	<a href="#">Link</a>




**Ersetzt alle bisherigen Preislisten.**

**Remplace et annule les précédentes listes de prix.**




**Artikel mit grau unterlegtem Händlercode sind Neuheiten oder haben eine Preisänderung erfahren.  
Articles avec code client gris sont des nouveautés ou ont changé de prix.**

**Bei Artikeln mit unterstrichenem Händlercode bitte Verfügbarkeit anfragen!  
Articles avec code client souligné demandez leur disponibilité!**





## Multi-Cellular Loudspeaker Systems

	<b>MLA</b>	Multi-cellular powered loudspeaker system	<u>C2</u>	a.A.
	<b>MLA Compact</b>	Multi-cellular powered loudspeaker system	<u>C2</u>	a.A.
	<b>MLA Mini</b>	Multi cellular miniature loudspeaker system	<u>C2</u>	a.A.









## Wavefront Precision Series

	<b>WPM</b>	Compact line array element, 2-way, 2x6.5"/ 3x1.4", System Amplifier iK42/iK81, Frequenz 76Hz-18kHz +/- 3dB, Max. SPL@1m 130dB peak, 100° hor., 10° vert., 2xNL4, 3-point rigging system, 2 x side pocket handles, 2x rear grip handles,	<u>C3</u>	3'160.–
	<b>WPM-W</b>	Dito, <b>white</b>	<u>C3</u>	3'160.–
	<b>WPC</b>	Compact line array element, 3-way, bi-amp, 2x10"/ 2x5"/ 4x0.7", System Amplifier iK42, Frequenz 65Hz-18kHz +/- 3dB, Max. SPL@1m 135dB peak, 100° hor., 10° vert., 2xNL4, 3-point rigging system, 2 x side pocket handles, 2x rear grip handles,	<u>C3</u>	6'395.–
	<b>WPC-W</b>	Dito, <b>white</b>	<u>C3</u>	6'395.–
	<b>WPL</b>	Compact line array element, 3-way, bi-amp, 2x12"/ 2x6.5"/ 3x1", System Amplifier iK42, Frequenz 52Hz-18kHz +/- 3dB, Max. SPL@1m LF:139dB / MF:140dB / HF:145dB, 120° hor., 7.5° vert., 2xNL4, 3-point rigging system, 4 x side pocket handles	<u>C3</u>	11'450.–

## Subwoofer - Wavefront Precision Series






	<b>SXF115</b>	Compact, direct radiating subwoofer 15", 800W AES / 3200W peak @ 4Ω, System Amplifier iK42/iK81, Frequenz 50Hz-150Hz +/- 3dB, Max. SPL@1m 136dB peak, 2xNL4, 1 x bar handles, pole mounting	<u>C3</u>	3'995.–
	<b>SX118</b>	Compact, direct radiating subwoofer 18", 1000W AES / 4000W peak @ 8Ω, System Amplifier iK42/iK81, Frequenz 47Hz-150Hz +/- 3dB, Max. SPL@1m 138dB peak, 2xNL4, 1 x bar handles, 16x M10 mounting points, 4x rear-mounted castors	<u>C3</u>	2'370.–
	<b>SX118-W</b>	Ditto, <b>white</b>	<u>C3</u>	2'370.–
	<b>SX218</b>	Dual-driver, direct radiating subwoofer 2x 18", 2000W AES / 8000W peak @ 2x 8Ω, System Amplifier iK42/iK81, Frequenz 35Hz-150Hz +/- 3dB, Max. SPL@1m 144dB peak, 2xNL4, 4 x bar handles, 24x M10 mounting points, 4x rear-mounted castors	<u>C3</u>	3'950.–
	<b>SX218-W</b>	Ditto, <b>white</b>	<u>C3</u>	3'950.–
	<b>SXH218</b>	Hybrid® Horn/Reflex Subwoofer 2x 18", 3000W AES / 12000W peak @ 4Ω, System Amplifier iK42, Frequenz 32Hz-150Hz +/- 3dB, Max. SPL@1m 148dB peak, 2xNL4, 6 x bar handles, 4x rear-mounted castors	<u>C3</u>	6'580.–

**Diverses Zubehör wie: Tour/Install Flybar, Dolly System, Transition Frame etc. auf Anfrage!**






O-Line 4 Pack				
	<b>O-Line</b>	2 x 3.5" scalable, 2-way, micro-line array, 4 cabinet array (Picture: 2 x Omniline 4 pack - price per 4-pack!)		
		Tech. spec. per module: 50W AES, 200W peak, 84-92 dB 1W/1m, 100° hor., 5° vert., 16Ω, light grey	<u>C3</u>	3'265.-
		Tech. spec. per 4 pack: 200W AES, 800W peak, 96dB 1W/1m, 4Ω, 14.4kg		
Accessories				
	<b>ASF20023</b>	Flying Bracket	<u>C3</u>	375.-
	<b>ASF20021</b>	Wall Bracket for 1 x 4-Pack O-Line Array	<u>C3</u>	375.-
	<b>ASF20022</b>	Wall Bracket for 2-3 x 4-Pack O-Line Arrays	<u>C3</u>	935.-
Differential Dispersion™ systems				
	<b>DD12</b>	Aktive, network enabled differential dispersion™ system 12"/1", 1050W Class-D, DSP, hor. 110°-60°, 60° vert., user rotatable, 125dB cont./ 131 dB peak, 15XM8 inserts, 2 x side pocket handles	<u>C3</u>	7'825.-
	<b>W8VDQ</b>	Compact 3-way differential dispersion™ system, 4x8"/4x1", LF+MF: 800W AES/ 3200 W peak, HF: 150W AES/ 600W peak, LF+MF: 102dB 1W/1m, HF: 106dB, 6Ω, 120°-100° hor, 30° vert., 9xM10, 4xM6 inserts, pole mount socket, 2 x bar handles	<u>C3</u>	7'120.-
	<b>DD6</b>	Ultra-compact differential dispersion™ system, 6.5"/0.5", 150W AES, 600 W peak, 91dB 1W/1m, 16Ω, 120°-90° hor, 60° vert., user rotatable tweeter, 8xM8, 4xM6 inserts, integrated pocket handle	<u>C3</u>	1'675.-
XD Series				
	<b>XD15</b>	Very high output 15"/1.4", LF: 600W AES/ 2400W peak, HF: 80W/ 320W peak, 99dB 1W/1m, 8Ω, 80° hor., 50° vert. (user rotatable), 17xM8 inserts, 1 x pole mounting socket, 2 x pocket handle	<u>C3</u>	3'720.-
	<b>XD12</b>	Compact high output 12"/1", LF: 400W AES/ 1600W peak, HF: 50W/ 200W peak, 98dB 1W/1m, 8Ω, 80° hor., 50° vert. (user rotatable), 21xM8 inserts, 1 x pole mounting socket, 1 x pocket handle	<u>C3</u>	2'320.-
PSX – Subwoofers for XD12, XD15 and DD6				
	<b>ASF10124</b>	15" Self-powered Subwoofer Class D, DSP, networking 1400W Sub + 1000W Full-range, (for XD12, XD15 and DD6).	<u>C3</u>	10'115.-




Accessories – DD Series / XD Series				
	<b>ASF20025</b>	W8VDQ yoke assembly	<u>C3</u>	935.–
	<b>ASF20034</b>	DD6 universal bracket	<u>C3</u>	240.–
	<b>ASF20035</b>	DD6 flying yoke	<u>C3</u>	150.–
	<b>ASF20036</b>	DD6 wall bracket	<u>C3</u>	190.–
	<b>ASF20045</b>	Universal 35mm pole mount adaptor, ASF20046 / ASF20048	<u>C3</u>	75.–
	<b>COV00028</b>	DD12 Cover	<u>C3</u>	305.–
	<b>ASF20046</b>	XD12 / DD12 / universal bracket	<u>C3</u>	720.–
	<b>ASF20048</b>	XD15 universal bracket	<u>C3</u>	720.–
	<b>ASF20047</b>	XD12 / DD12 yoke	<u>C3</u>	390.–
	<b>ASF20049</b>	XD 15 yoke	<u>C3</u>	440.–
	<b>HTKM20</b>	XD12 wall bracket (per pair!)	<u>C3</u>	295.–
TH Series				
	<b>THH</b>	3-way bi-amp trapezoid Hybrid® fully horn loaded, 15"/10"/1", LF: 750W AES@8Ohm, MF+HF: 300W AES@8Ohm, Frequenz 50Hz-18kHz ± 3dB, Max. SPL@1m 139dB peak, 70° hor., 40° vert., 4xNL4, 4 x pocket handles, 12 x M10 inserts	<u>C3</u>	5'130.–
	<b>THV</b>	Dito, <b>Vertical</b>	<u>C3</u>	5'130.–
Stage Monitors				
	<b>LE100</b>	2-way passive, Coaxial Differential Dispersion, 12"/1", 300W AES / 1200W peak @ 8Ω, Frequenz 78Hz-20kHz +/- 3dB, Max. SPL@1m 129dB peak, 110° hor., 60° vert., 5xNL4,	<u>C3</u>	1'895.–
	<b>LE200</b>	2-way passive, bi-amp, Coaxial Differential Dispersion, 15"/1.4", 400W AES / 1600W peak @ 8Ω, Frequenz 68Hz-18kHz +/- 3dB, Max. SPL@1m 133dB peak, 110°-60° hor., 60° vert., 4xNL4,	<u>C3</u>	2'365.–
	<b>XE300</b>	2-way passive, bi-amp, Coaxial Differential Dispersion, 12"/1.4", LF: 350W AES/ 1400W peak @ 6Ω, HF: 80W AES/ 320W peak @ 8Ω, System Amplifier iK42, Frequenz 67Hz-18kHz +/- 3dB, Max. SPL@1m 139dB peak, 60°-30° hor., 90° vert., 4xNL4	<u>C3</u>	3'160.–
	<b>XE500</b>	2-way passive, bi-amp, Coaxial Differential Dispersion, 15"/1.4", LF: 550W AES/ 2200W peak @ 4Ω, HF: 80W AES/ 320W peak @ 8Ω, System Amplifier iK42, Frequenz 62Hz-18kHz +/- 3dB, Max. SPL@1m 143dB peak, 60°-30° hor., 70° vert., 4xNL4	<u>C3</u>	4'265.–

## CDD Live - Powered, Dante

	<b>CDD-LIVE8B</b> Powerd - Coax 8"/1", 1300W, <b>black</b> , Dante, DSP, 110°-80° hor., 60° vert. (user rotatable), 15xM8 inserts, (W)258mm x (H)428mm x (D)254mm	<u>C3</u>	2'985.-
	<b>CDD-LIVE8W</b> Dito, <b>white</b>	<u>C3</u>	2'985.-
	<b>CDD-LIVE12B</b> Powerd - Coax 12"/1", 2500W, <b>black</b> , Dante, DSP, 110°-80° hor., 60° vert. (user rotatable), 15xM8 inserts, (W)359mm x (H)580mm x (D)373mm	<u>C3</u>	4'105.-
	<b>CDD-LIVE12W</b> Dito, <b>white</b>	<u>C3</u>	4'105.-
	<b>CDD-LIVE15B</b> Powerd - Coax 15"/1.4", 2500W, <b>black</b> , Dante, DSP, 100°-60° hor., 60° vert. (user rotatable), 15xM8 inserts, (W)427mm x (H)696mm x (D)422mm	<u>C3</u>	4'665.-
	<b>CDD-LIVE15W</b> Dito, <b>white</b>	<u>C3</u>	4'665.-
	<b>CSX-LIVE118B</b> Powerd - Subwoofer 18", 2000W, <b>black</b> , Dante, DSP, (W)600mm x (H)509mm x (D)632mm	<u>C3</u>	5'055.-
	<b>CSX-LIVE118W</b> Dito, <b>white</b>	<u>C3</u>	5'055.-
	<b>CSX-LIVE218B</b> Powerd - Subwoofer 2x 18", 4000W, <b>black</b> , Dante, DSP, (W)1085mm x (H)537mm x (D)792mm	<u>C3</u>	8'035.-
	<b>CSX-LIVE218W</b> Dito, <b>white</b>	<u>C3</u>	8'035.-

## CDD Live - Accessories








	<b>CDDCB6/8B</b> Ceiling bracket for CDD-Live 8, <b>black</b>	C3	120.-
	<b>WB6/8B</b> Wall bracket for CDD-Live 8, <b>black, weatherised</b>	C3	95.-
	<b>WB6/8W</b> Dito, <b>white</b>	C3	95.-
	<b>WB10/12B</b> Wall bracket for CDD-Live 12, <b>black, weatherised</b>	C3	115.-
	<b>WB10/12W</b> Dito, <b>white</b>	C3	115.-
	<b>CDDLUB8B</b> Universal bracket for CDD-Live 8, <b>black</b>	<u>C3</u>	235.-
	<b>ASF20046</b> Universal bracket for CDD-Live 12, <b>black</b>	<u>C3</u>	720.-
	<b>ASF20048</b> Universal bracket for CDD-Live 15, <b>black</b>	<u>C3</u>	720.-

	<b>CDDL YA8B</b>	Yoke assembly for CDD-Live 8, <b>black</b>	<u>C3</u>	355.–
	<b>CDDL YA12B</b>	Yoke assembly for CDD-Live 12, <b>black</b>	<u>C3</u>	395.–
	<b>CDDL YA15B</b>	Yoke assembly for CDD-Live 15, <b>black</b>	<u>C3</u>	410.–
	<b>HTK00003</b>	8mm shouldered eye bolt for CDD Live 8, 12, 15	<u>C3</u>	55.– (Stück)
	<b>HTK00004</b>	10mm shouldered eye bolt for CSX Live 118, 218	<u>C3</u>	60.– (Stück)
	<b>ASF20045</b>	Universal 35mm pole mount adaptor	<u>C3</u>	75.–
	<b>CDDLTC8</b>	Transit Cover for CDD-Live 8	<u>C3</u>	195.–
	<b>CDDLTC12</b>	Transit Cover for CDD-Live 12	<u>C3</u>	235.–
	<b>CDDLTC15</b>	Transit Cover for CDD-Live 15	<u>C3</u>	270.–
	<b>CDDLTC118</b>	Transit Cover for CDD-Live 118	<u>C3</u>	595.–
	<b>CDDLTC218</b>	Transit Cover for CDD-Live 218	<u>C3</u>	805.–
	<b>CDDL RK8</b>	Rain Kit Upgrade for CDD-Live 8	<u>C3</u>	365.–
	<b>CDDL RK12</b>	Rain Kit Upgrade for CDD-Live 12	<u>C3</u>	550.–
	<b>CDDL RK15</b>	Rain Kit Upgrade for CDD-Live 15	<u>C3</u>	645.–
	<b>CDDL RK118/218</b>	Rain Kit Upgrade for CDD-Live 118/218	<u>C3</u>	550.–




CDD Series		VPE			
	<b>CDD5B</b>	Coax 5,25"/0.75", 100W @8 Ω AES, <b>black</b> , 120°-90° hor., 80° vert. (user rotatable), 6xM5 inserts, (W)160mm x (H)230mm x (D)149mm, <b>(Incl. Wall bracket)</b>	2	C3	280.–
	<b>CDD5W</b>	Dito, <b>white</b>	2	C3	280.–
	<b>CDD5BTX-WR</b>	Dito, 100W @8Ω AES, 6/12.5/25W @100V, <b>black, weatherised</b>	2	<u>C3</u>	415.–
	<b>CDD5WTX-WR</b>	Dito, 100W @8Ω AES, 6/12.5/25W @100V, <b>white, weatherised</b>	2	<u>C3</u>	415.–
	<b>CDD6B</b>	Coax 6,5"/1", 150W @8Ω AES, <b>black</b> , 110°-80° hor., 80° vert. (user rotatable), 4 x M6 inserts, (W)210mm x (H)325mm x (D)210mm	2	C3	485.–
	<b>CDD6W</b>	Dito, <b>white</b>	2	C3	485.–
	<b>CDD6BTX-WR</b>	Dito, 150W @8Ω AES, 12.5/25/50W @100V, <b>black, weatherised</b>	2	<u>C3</u>	775.–
	<b>CDD6WTX-WR</b>	Dito, 150W @8Ω AES, 12.5/25/50W @100V, <b>white, weatherised</b>	2	<u>C3</u>	775.–
	<b>CDD8B</b>	Coax 8"/1", 200W @8Ω AES, <b>black</b> , 110°-80° hor., 60° vert. (user rotatable), 6xM6 inserts, (W)256mm x (H)410mm x (D)253mm		C3	935.–
	<b>CDD8W</b>	Dito, <b>white</b>		C3	935.–
	<b>CDD8B-WR</b>	Dito, <b>black, weatherised</b>		<u>C3</u>	1'205.–
	<b>CDD8W-WR</b>	Dito, <b>white, weatherised</b>		<u>C3</u>	1'205.–
	<b>CDD10B</b>	Coax 10"/1", 250W @8Ω AES, <b>black</b> , 110°-75° hor., 60° vert. (user rotatable), 6xM8 inserts, 10xM8 fly points (W)323mm x (H)515mm x (D)311mm		C3	1'285.–
	<b>CDD10W</b>	Dito, <b>white</b>		C3	1'285.–
	<b>CDD10B-WR</b>	Dito, <b>black, weatherised</b>		<u>C3</u>	1'685.–
	<b>CDD10W-WR</b>	Dito, <b>white, weatherised</b>		<u>C3</u>	1'685.–
	<b>CDD12B</b>	Coax 12"/1", 300W @8Ω AES, <b>black</b> , 110°-60° hor., 60° vert. (user rotatable), 6xM8 inserts, 10xM8 fly points, (W)357mm x (H)571mm x (D)348mm		C3	1'610.–
	<b>CDD12W</b>	Dito, <b>white</b>		<u>C3</u>	1'610.–
	<b>CDD12B-WR</b>	Dito, <b>black, weatherised</b>		<u>C3</u>	2'010.–
	<b>CDD12W-WR</b>	Dito, <b>white, weatherised</b>		<u>C3</u>	2'010.–
	<b>CDD15B</b>	Coax 15"/1.4", 400W @8Ω AES, <b>black</b> , 100°-60° hor., 60° vert. (user rotatable), 10xM8 fly points, (W)425mm x (H)691mm x (D)411mm		C3	2'195.–
	<b>CDD15W</b>	Dito, <b>white</b>		<u>C3</u>	2'195.–
	<b>CDD15B-WR</b>	Dito, <b>black, weatherised</b>		<u>C3</u>	2'610.–
	<b>CDD15W-WR</b>	Dito, <b>white, weatherised</b>		<u>C3</u>	2'610.–

## CDD Series - Accessories









	<b>WB6/8B</b>	Wall bracket for CDD6B - CDD8B- CDD6BTX-WR - CDD8B-WR, <b>black, weatherised</b>	C3	95.–
	<b>WB6/8W</b>	Dito, <b>white, weatherised</b>	C3	95.–
	<b>CDDWB10/12B</b>	Wall bracket for CDD10B - CDD12B, <b>black</b>	C3	115.–
	<b>CDDWB10/12W</b>	Dito, <b>white</b>	C3	115.–
	<b>WB10/12B</b>	Wall bracket for CDD10B-WR - CDD12B-WR, <b>black, weatherised</b>	<u>C3</u>	115.–
	<b>WB10/12W</b>	Dito <b>white, weatherised</b>	<u>C3</u>	115.–
	<b>CDDCB5B-WR</b>	Ceiling bracket for CDD5BTX-WR – CDD5B, <b>black, weatherised</b>	C3	75.–
	<b>CDDCB5W-WR</b>	Dito, <b>white, weatherised</b>	C3	75.–
	<b>CDDCB6/8B-WR</b>	Ceiling bracket for CDD6W – CDD8B - CDD6W-WR or CDD8W-WR, <b>black, weatherised</b>	C3	120.–
	<b>CDDCW6/8W-WR</b>	Dito, <b>white</b>	C3	120.–
	<b>CDDYA10B-WR</b>	Yoke assembly for CDD10B - CDD10B-WR, <b>black, weatherised</b>	C3	320.–
	<b>CDDYA10W-WR</b>	Dito, <b>white, weatherised</b>	<u>C3</u>	320.–
	<b>CDDYA12B</b>	Yoke assembly for CDD12B, <b>black</b>	C3	239.–
	<b>CDDYA12B-WR</b>	Yoke assembly for CDD12B-WR, <b>black, weatherised</b>	<u>C3</u>	335.–
	<b>CDDYA12W-WR</b>	Dito, <b>white, weatherised</b>	C3	335.–
	<b>CDDYA15B-WR</b>	Yoke assembly for CDD15B - CDD15B-WR, <b>black, weatherised</b>	C3	355.–
	<b>CDDYA15W-WR</b>	Yoke assembly for CDD15W - CDD15W-WR <b>white, weatherised</b>	C3	355.–



<b>BlacklineX Series</b>				
	<b>X8B</b>	2-way 8"/1", 200W@8Ω AES, 90° hor., 50° vert. (user rotatable), 13xM8 - 6xM6 inserts, pole-mount socket, pocket handle, (W)257mm x (H)422mm x (D)243mm	<u>C3</u>	555.–
	<b>X8W</b>	Dito, <b>white</b>	<u>C3</u>	790.–
	<b>X10B</b>	2-way 10"/1", 250W@8Ω AES, 90° hor., 50° vert. (user rotatable), 19xM8, pole-mount socket, bar handle, (W)324mm x (H)522mm x (D)289mm	<u>C3</u>	930.–
	<b>X10W</b>	Dito, <b>white</b>	<u>C3</u>	1'175.–
	<b>X12B</b>	2-way 12"/1", 300W@8Ω AES, 80° hor., 50° vert. (user rotatable), 20xM8 - 6xM6 inserts, pole-mount socket, bar handle, (W)358mm x (H)574mm x (D)337mm	<u>C3</u>	1'120.–
	<b>X12W</b>	Dito, <b>white</b>	<u>C3</u>	1'395.–
	<b>X15B</b>	2-way 15"/1", 400W@8Ω AES, 80° hor., 50° vert. (user rotatable), 19xM8 - 6xM6 inserts, pole-mount socket, bar handle, (W)427mm x (H)690mm x (D)419mm	C3	1'395.–
	<b>X15W</b>	Dito, <b>white</b>	<u>C3</u>	1'770.–
<b>BlacklineX Series – Accessories</b>				
	<b>WB6/8B</b>	Wall bracket for X8B, <b>black, weatherised</b>	C3	95.–
	<b>WB6/8W</b>	Dito, <b>white, weatherised</b>	C3	95.–
	<b>CDDWB10/12B</b>	Wall bracket for X10B - X12B - X15B, <b>black</b>	C3	115.–
	<b>CDDWB10/12W</b>	Dito, <b>white</b>	C3	115.–
	<b>HTKCT04</b>	Pole for BlacklineX	<u>C3</u>	45.–
	<b>HTK00003</b>	8mm shouldered eye bolt for X8 - X12	<u>C3</u>	55.– (Stück)
	<b>HTK00004</b>	10mm shouldered eye bolt for X15 - X115 - X118 - X210	<u>C3</u>	60.– (Stück)

Adorn - Series			VPE		
	<b>A40B</b>	2-way 4"/0.75", 40W@16Ω AES, 110° hor., 80° vert. (W)124mm x (H)200mm x (D)114mm, <b>(Incl. Wall bracket)</b>	2	<u>C3</u>	139.–
	<b>A40W</b>	Dito, <b>white</b>	2	<u>C3</u>	139.–
	<b>A40TB</b>	Dito, 40W@16Ω AES, 2.5/5/10W@100V	2	<u>C3</u>	179.–
	<b>A40TW</b>	Dito, <b>white</b>	2	<u>C3</u>	179.–
	<b>A55B</b>	2-way 5.25"/0.75", 50W@16Ω AES, 110° hor., 80° vert. (W)152mm x (H)245mm x (D)140mm, <b>(Incl. Wall bracket)</b>	2	<u>C3</u>	179.–
	<b>A55W</b>	Dito, <b>white</b>	2	<u>C3</u>	179.–
	<b>A55TB</b>	Dito, 50W@16Ω AES, 7.5/15/30W@100V	2	<u>C3</u>	215.–
	<b>A55TW</b>	Dito, <b>white</b>	2	<u>C3</u>	215.–
	<b>AIPKIT</b>	IP44 Connector cover for A40 and A55 Series	2	<u>C3</u>	15.–
Adorn Series - Accessories					
	<b>CDDCB5B-WR</b>	Ceiling bracket for CDD5BTX-WR – CDD5B, <b>black, weatherised</b>		<u>C3</u>	75.–
	<b>CDDCB5W-WR</b>	Dito, <b>white, weatherised</b>		<u>C3</u>	75.–
Subwoofer – BlacklineX, CSX					
	<b>SX110B</b>	Subwoofer 10", 250W8Ω AES, <b>black</b> (W)417mm x (H)297mm x (D)415mm		<u>C3</u>	610.–
	<b>SX110W</b>	Dito, <b>white</b>		<u>C3</u>	685.–
	<b>X210B</b>	Subwoofer 2x 10", 500W@4Ω AES, 16xM8 inserts, bar handle, (W)720mm x (H)295mm x (D)465mm, 20Kg		<u>C3</u>	1'490.–
	<b>X210W</b>	Dito, <b>white</b>		<u>C3</u>	1'865.–
	<b>CSX112B-F</b>	Subwoofer 12", 400W8Ω AES, <b>black, flown</b> (W)487mm x (H)385mm x (D)410mm		<u>C3</u>	1'325.–
	<b>CSX112W-F</b>	Dito, <b>white</b>		<u>C3</u>	1'325.–
	<b>CSX112B-FWR</b>	Dito, <b>black, weatherised</b>		<u>C3</u>	1'785.–
	<b>CSX112W-FWR</b>	Dito, <b>white, weatherised</b>		<u>C3</u>	1'785.–
	<b>CSX212B-F</b>	Subwoofer 2x 12", 800W4Ω AES, <b>black, flown</b> (W)872mm x (H)385mm x (D)437mm		<u>C3</u>	2'080.–
	<b>CSX212W-F</b>	Dito, <b>white</b>		<u>C3</u>	2'080.–
	<b>CSX212B-FWR</b>	Dito, <b>black, weatherised</b>		<u>C3</u>	2'555.–
	<b>CSX212W-FWR</b>	Dito, <b>white, weatherised</b>		<u>C3</u>	2'555.–

	<b>X115B</b>	Subwoofer 15", 500W@8Ω AES, 16xM10 inserts, pole-mount socket, bar handle, provision for castors, (W)465mm x (H)590mm x (D)565mm, 27Kg		<u>C3</u>	1'120.–
	<b>X115W</b>	Dito, <b>white</b>		<u>C3</u>	1'490.–
	<b>X118B</b>	Subwoofer 18", 500W@8Ω AES, 16xM10 inserts, pole-mount socket, bar handle, provision for castors, (W)530mm x (H)669mm x (D)640mm, 33Kg		<u>C3</u>	1'395.–
	<b>X118W</b>	Dito, <b>white</b>		<u>C3</u>	1'860.–
	<b>CSX118B-F</b>	Subwoofer 18", 1000W8Ω AES, <b>black, flown</b> (W)662mm x (H)530mm x (D)640mm		<u>C3</u>	1'935.–
	<b>CSX118W-F</b>	Dito, <b>white</b>		<u>C3</u>	1'935.–
	<b>CSX118B-FWR</b>	Dito, <b>black, weatherised</b>		<u>C3</u>	2'465.–
	<b>CSX118W-FWR</b>	Dito, <b>white, weatherised</b>		<u>C3</u>	2'465.–
	<b>CSX218B-F</b>	Subwoofer 2x 18", 2000W4Ω AES, <b>black, flown</b> (W)1085mm x (H)530mm x (D)780mm		<u>C3</u>	3'865.–
	<b>CSX218W-F</b>	Dito, <b>white</b>		<u>C3</u>	3'865.–
	<b>CSX218B-FWR</b>	Dito, <b>black, weatherised</b>		<u>C3</u>	4'760.–
	<b>CSX218W-FWR</b>	Dito, <b>white, weatherised</b>		<u>C3</u>	4'760.–
<b>Ceiling Series</b>			<b>VPE</b>		
	<b>C4.8T</b>	2-Way ceiling speaker, 4"/0.8", 40W AES, 160W peak, 16Ω, 25/12.5/6W@100V, Ø 205mm, cut out Ø 178mm, <b>white</b>	2	<u>C3</u>	185.–
	<b>C6.8T</b>	2-Way ceiling speaker, 6.5"/0.8", 75W AES, 300W peak, 16Ω, 40/20/10W@100V, Ø 260mm, cut out Ø 224mm, <b>white</b>	2	<u>C3</u>	265.–
	<b>C8.1T</b>	2-Way ceiling speaker, 8"/0.8", 125W AES, 500W peak, 16Ω, 60/30/15W@100V, Ø 354mm, cut out Ø 308mm, <b>white</b>	2	<u>C3</u>	410.–
<b>Accessories</b>					
	<b>GEB-C4</b>	Housing for setting in concrete for C4.8T	1	<u>C3</u>	79.–
	<b>GEB-C6</b>	Housing for setting in concrete for C6.8T	1	<u>C3</u>	79.–

Amplifiers				
	<b>iK42</b>	4 channel Class D amplifier, 20'000 Watts RMS all channels driven, (5000W per channel @ 2Ω) 96kHz DSP inputs and outputs, Analogue, AES3, Dante, Ethernet, Powercon™, 8Kg	<u>C3</u>	9'165.–
	<b>iK81</b>	8 channel Class D amplifier, 10'000 Watts RMS all channels driven (1250W per channel @ 2/4/8Ω) 96kHz DSP inputs and outputs, Analogue, AES3, Dante, Ethernet, Powercon™, 12.5Kg	<u>C3</u>	10'685.–
	<b>VIA2004</b>	Class D, 4x 500W@4Ω, 4x 250W@8Ω, 8Kg	<u>C3</u>	1'835.–
	<b>VIA2502</b>	Class D, 2x 1250W @2Ω, 2x 800W@4Ω, 2x 450W@8Ω, 8Kg	<u>C3</u>	2'670.–
	<b>VIA5002</b>	Class D, 2x 2500W@4Ω, 2x 1600W@8Ω, 10Kg	<u>C3</u>	4'885.–
	<b>VIA5004</b>	Class D, 4x 1250W @2Ω, 4x 800W@4Ω, 4x 450W@8Ω, 10Kg	<u>C3</u>	4'885.–
Controllers				
	<b>DX0.5</b>	2:6 loudspeaker processor, 2.6Kg	<u>C3</u>	1'010.–
	<b>DX4.0</b>	4:8 loudspeaker processor, analogue, AES3, Dante, 2.7Kg	<u>C3</u>	3'585.–