



Der Vertrieb der PanAcoustics Produkte erfolgt durch den autorisierten Fachhandel. Fragen Sie uns an, wir helfen Ihnen sehr gerne weiter.

Standard colours: RAL 9006 (aluminium) or RAL-9010 (white) or RAL-9005 (black)
Standard delivery is **without mounting** brackets


Pan 2-Line

	PB 04-P2L	Compact active digitally controllable column speaker with Beam Steering Technology, Drivers: 4 x 3.5 "wide band chassis, amplifier output power: 4 x up to 40 watt, Pan 2-Line I/O: 1 x 5-pin connector (audio, controll data and power), colour: RAL 9006 aluminium		
	PB 07-P2L	Compact active digitally controllable column speaker with Beam Steering Technology (single Beam), Drivers: 7 x 2.1" wide band chassis, amplifier output power: 4 x up to 25 watt, Pan 2-Line I/O: 1 x five-wire connector (audio, controll data and power)		
	PB 08-P2L	Compact active digitally controllable column speaker with Beam Steering Technology, Drivers: 8 x 3.5" wide band chassis, amplifier output power: 8 x up to 40 watt, Pan 2-Line I/O: 1 x 5-pin connector (audio, controll data and power), colour: RAL 9006 aluminium		
	PB 15-P2L	Compact active digitally controllable column speaker with Beam Steering Technology (single Beam), Drivers: 15 x 2.1" wide band chassis, amplifier output power: 8 x up to 25 watt, Pan 2-Line I/O: 1 x 5-pin connector (audio, controll data and power)		
	PB 16-C-P2L	Compact active digitally controllable column speaker with Beam Steering Technology, Drivers: 16 x 3.5 "wide band chassis, amplifier output power: 16 x up to 20 watt, Pan 2-Line I/O: 1 x 5-pin connector (audio, controll data and power), PB 16-C-PPL consist of tow modules with internal link, colour: RAL 9006 aluminium		
	PB 16-C-P2L (one housing)	Compact active digitally controllable column speaker with Beam Steering Technology, Drivers: 16 x 3.5 "wide band chassis, amplifier output power: 16 x up to 20 watt, Pan 2-Line I/O: 1 x 5-pin connector (audio, controll data and power), colour: RAL 9006 aluminium		
	PB 16-P2L	Compact active digitally steerable line array in column design with Beam Steering Technology, drivers: 16 x 3.5" HQ, amplifier output power: 16 x up to 40 watts, Pan 2-Line I/O: 1 x 5-pin connector (audio, control data and power), PB 16-P2L consists of two modules with internal link		
	PB 16-P2L (one housing)	One housing active digitally steerable line array in column design with Beam Steering Technology, drivers: 16 x 3.5" HQ, amplifier output power: 16 x up to 40 watts, Pan 2-Line I/O: 1 x 5-pin connector (audio, control data and power) , PB 16-P2L consists of one housing		






Pan Powerline – Control Unit Series





	CCU 2/2-P2L	Central control unit for Pan Powerline system, with two 2-Line outputs (each 200 Watt), each Output has a separate audio input (XLR), preset selector for switching stored presets at connected devices, interface for external media control		
	CCU 4/4-P2L	Central control unit for Pan Powerline system, with four 2-Line outputs (each 200 Watt), each Output has a separate audio input (XLR), preset selector for switching stored presets at connected devices, interface for external media control		

Colour option (RAL-XXXX, powder coated, three gloss levels)

	The painting refers to housing and grids in the same colour, different colours (housing, grid) are available on request.		
	CO 04	Colour option RAL-xxxx for Px 04-x	
	CO 08	Colour option RAL-xxxx for Px 08-x	
	CO 16	Colour option RAL-xxxx for Px 16-x	
	CO wall mount	Colour option RAL-xxxx for wall mount (without screws)	
	CO stand base	Colour option RAL-xxxx for stand base P/PB	
	Default colour for all Pan Beam products is aluminium RAL 9006, or RAL-9010 (white) or RAL-9005 (black), unless another colour information is specified for a product. Usually all products are powdered. colour have to choose by order, with RAL xxxx (4-bit code) and gloss level. Other colour systems are possible, like RAL (3-bit code), NCS, Pantone, DB etc, on request.		

Mounting accessories

	fixed wall mount	Wall-mount kit for mounting Pan Column-Speaker on wall, vertical 0°/4° in stainless steel. For Pan Speaker, Pan 2-Line, Pan Beam, Pan AMT Speakers. (Art. 801840).		
	rotable wall mount (TWM II)	Swivel wall-mount kit for mounting Pan Column-Speaker on wall (bottom and top) in stainless steel. For Pan Speaker, Pan 2-Line, Pan Beam, Pan AMT Speakers. (Art. 801840).		
	horizontally rotatable wall mount (TWM III)	Wall-mount horizontal turnable kit in stainless steel. For Pan Speaker, Pan 2-Line, Pan Beam, Pan AMT Speakers (Art. 801841)		
	stand holder P / PB xx	Stand mount (35mm) in stainless steel. For Pan Speaker, Pan 2-Line, Pan Beam small, Pan AMT small (Art. 801843)		
	wall mount, tiltable, turnable (black)	Universal wall mount (horizontal 180° and vertical 0-15° adjustment), up to 10 kg load, incl. Sliding block, standard colour: black (Art. 801449)		
	wall mount, tiltable, turnable (white)	Universal wall mount (horizontal 180° and vertical 0-15° adjustment), up to 10 kg load, incl. Sliding block, standard colour: white (art. 801450)		

	<p>ceiling mount, fix, (black) PB xx</p> <p>Robust and useful loudspeaker ceiling mount with 250 mm distance and internal cable management. The swivel area is +/- 45 °. Within the parameters - the settings range from 0 to 45°. Max. load is 25kg. The clamping bracket is for loudspeakers with a vertical mounting template from 70 to 76.2 mm. For other attachment possibilities additional adapter brackets are available. A mounting bracket with side and central cable management makes mounting to the ceiling easier. incl. slider block, standard colour: black (art. 801451)</p>		
	<p>Ceiling mount, fix, (white) PB xx</p> <p>Dito ceiling mount, fix, (black) PB xx but white (art. 801452)</p>		
	<p>Telescop ceiling mount, flex, (black) PB xx</p> <p>Flexible ceiling mount with variable length 700-1200mm incl. slider block, standard colour: black (art. 802406)</p>		
	<p>Telescop ceiling mount, flex, (white) PB xx</p> <p>Flexible ceiling mount with variable length 700-1200mm incl. slider block, standard colour: white (art. 801285)</p>		
	<p>Stand base P/PB</p> <p>High quality base for Pan Beam & Pan Speaker series with rectangular steel base plate 60x30 cm. P / PB xx loudspeakers (consisting of a maximum of two modules) can be mounted on the base. (Art. 803995)</p>		

**Ersetzt alle bisherigen Preislisten.
Remplace toutes les listes de prix anciennes.**

**Artikel mit grau unterlegtem Händlercode sind Neuheiten oder haben eine Preisänderung erfahren.
Articles avec code client gris sont des nouveautés ou ont changé de prix.**

**Bei Artikeln mit unterstrichenem Händlercode bitte Verfügbarkeit anfragen!
Articles avec code client souligné demandez leur disponibilité.**